

GC Secondary Barrier Testing Requirements

12

(Sept
2007)

(Corr.1
Nov
2007)

The International Code for the Construction and Equipment of Ships Carrying Liquid Gases in Bulk (IBGC Code), 4.7.7 reads:

"The secondary barrier should be capable of being periodically checked for its effectiveness, by means of a pressure/vacuum test, a visual inspection or another suitable method acceptable to the Administration. The method should be submitted to the Administration for approval."

Paragraph 4.7.7 shall be interpreted as follows:

For containment systems with glued secondary barriers:

- A tightness test should be carried out in accordance with approved system designers' procedures before and after initial cool down.
- If significant differences in the results before and after cool down for each tank or between tanks or if other anomalies are observed, an investigation is to be carried out and additional testing such as differential pressure, thermographic or acoustic emissions testing should be carried out as necessary.
- The values recorded should be used as reference for future assessment of secondary barrier tightness.

For containment systems with welded metallic secondary barriers, a tightness test after initial cool down is not required.

Note:

~~This Unified Interpretation is to be applied by all Members and Associate from not later than 1 July 2008. However, Members and Associate are not precluded from applying this UI before this date.~~

This Unified Interpretation is to be applied by all Members and Associate to tests commenced on or after 1 July 2008.

End of Document
