
4 ALBERT EMBANKMENT
LONDON SE1 7SR
Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

MEPC.1/Circ.899
10 June 2022

**2022 GUIDELINES FOR RISK AND IMPACT ASSESSMENTS OF THE DISCHARGE
WATER FROM EXHAUST GAS CLEANING SYSTEMS**

1 The Marine Environment Protection Committee, at its seventy-eighth session (6 to 10 June 2022), approved the *2022 Guidelines for risk and impact assessments of the discharge water from exhaust gas cleaning systems*, as set out in the annex.

2 Member Governments are invited to bring the annexed Guidelines to the attention of Administrations, port State control authorities, industry, relevant shipping organizations, shipping companies and other stakeholders concerned.

3 The Committee agreed to keep these Guidelines under review in light of experience gained.

ANNEX

2022 GUIDELINES FOR RISK AND IMPACT ASSESSMENTS OF THE DISCHARGE WATER FROM EXHAUST GAS CLEANING SYSTEMS

CONTENTS

- 1 INTRODUCTION
- 2 DEFINITIONS AND ABBREVIATIONS
 - 2.1 Definitions
 - 2.2 Abbreviations
- 3 PRINCIPLES
- 4 APPLICATION
- 5 GENERAL REQUIREMENTS
 - 5.1 Targeted chemical substances and their data-set
 - 5.2 Information of the area to be assessed
- 6 RISK CHARACTERIZATION
 - 6.1 Introduction
 - 6.2 Emission scenarios
 - 6.3 Exposure assessment for PEC
 - 6.4 Human exposure scenarios
 - 6.5 Risk assessment
 - 6.6 Risk characterization and analysis
 - 6.7 Whole Effluent Toxicity
- 7 IMPACT ASSESSMENT
- 8 NOTIFICATION TO THE ORGANIZATION
- APPENDIX 1 GENERAL INFORMATION ON MAMPEC
- APPENDIX 2 HOW TO ESTIMATE HUMAN EXPOSURE

1 INTRODUCTION

1.1 These guidelines provide information on recommended methodology for risk and impact assessments that Member States should follow when considering local or regional regulations to protect the sensitive waters/environment from the discharge water from EGCS that complies with the Convention. These guidelines include assessments of the risks from a long-term perspective, with respect to aquatic quality, aquatic organism, and/or human health, and the impact assessment approach which may be applied to the specific receiving environment.

1.2 Member States are recommended to conduct an environmental risk assessment according to these guidelines when considering local or regional regulations.

1.3 The purpose of these guidelines is to provide a unified approach containing procedures that would support Member States to judge whether the introduction of restrictions/conditions of discharge water from EGCS would be needed and justifiable or not. In all aspects of risk and impact assessments the need for evidence-based decision-making should be balanced with the precautionary approach as set out in resolution MEPC.67(37).¹

2 DEFINITIONS AND ABBREVIATIONS

2.1 Definitions

2.1.1 For the purpose of these guidelines,

- .1 "Discharge water" means any water from an EGCS to be discharged overboard;
- .2 "Washwater" means cleaning medium brought into contact with the exhaust gas stream for the reduction of SO_x;
- .3 "Bleed-off water" means an amount of aqueous solution removed from the washwater of an EGCS operating in closed-loop mode to keep its required operating properties and efficiency;
- .4 "EGCS residue" means material removed from the washwater or the bleed-off water by a treatment system or discharge water that does not meet the discharge criterion, or other residue material removed from the EGCS;
- .5 "Emissions" means any release of substances, subject to control by this annex, from ships into the atmosphere or sea according to regulation 2.1.12 of MARPOL Annex VI²;
- .6 "Aggregated exposure approach" in relation to human exposure scenarios means the assessment of the total exposure to one substance resulting from more than one exposure pathway (inhalation, dermal and oral) and/or from more than one exposure scenario;

¹ *Guidelines on Incorporation of the precautionary approach in the context of specific IMO activities.*

² The regulation numbers in these Guidelines refer to the 2021 Revised MARPOL Annex VI, as adopted by resolution MEPC.328(76), which was accepted on 1 May 2022 in accordance with article 16(2)(f)(iii) of MARPOL and which will enter into force on 1 November 2022.

- .7 "Area to be assessed" means sea area where discharge water from EGCS is intended to be restricted under certain conditions;
- .8 "Emission factor" means the concentration of the product of individual substance in discharge water from EGCS per the typical flow rate, expressed as mg/MWh; and
- .9 "Sea Area for calculating PEC (SAP)" means sea area selected for simulation to estimate Predicted Environmental Concentrations (PECs) of the targeted chemicals, which should be a part of the area to be assessed.

2.1.2 Furthermore, the definitions in *2021 Guidelines for exhaust gas cleaning systems* adopted by resolution MEPC.340(77) apply.

2.2 Abbreviations

2.2.1 For the purpose of these guidelines, the following abbreviations apply.

| | |
|----------------------|---|
| 2021 EGCS Guidelines | <i>2021 Guidelines for Exhaust Gas Cleaning Systems</i> adopted by resolution MEPC.340(77) |
| AIS | Automatic Identification System |
| AIST | National Institute of Advanced Industrial Science and Technology of Japan |
| BCF | Bioconcentration Factor |
| BMD | Benchmark Dose |
| BMDL ₁₀ | Benchmark Dose Lower Confidence Limit 10% |
| CFD | Computational Fluid Dynamics |
| CMR | Carcinogenicity, Mutagenicity and Reproductive Toxicity |
| DMEL | Derived Minimal Effect Level |
| DNEL | Derived No-Effect Level |
| EFSA | European Food Safety Authority |
| EQS | Environmental Quality Standards |
| ERA | Environmental Risk Assessment |
| EUSES | European Union System for The Evaluation of Substances |
| GESAMP | IMO/FAO/UNESCOIOC/WMO/IAEA/UN/UNDP/UNEP/UNIDO Joint Group of Experts on the Scientific Aspects of Marine Environmental Protection |
| JECFA | Joint FAO/WHO Expert Committee on Food Additives |
| GESAMP EGCS TT | GESAMP Task Team on Exhaust Gas Cleaning Systems |
| K _{oc} | Organic Carbon-Water Partition Coefficient |
| K _p | Permeability Coefficient |
| MAMPEC | Marine Anti-Foulant Model for PEC Calculation |
| MOE | Margin of Exposure |
| NOAEL | No Observed Adverse Effect Level |
| PBT | Persistence, Bioaccumulation and Toxicity |
| PEC | Predicted Environmental Concentration |
| PNEC | Predicted No Effect Concentration |
| PTMI | Provisional Tolerable Monthly Intake |
| PTWI | Provisional Tolerable Weekly Intake |
| (Q)SAR | (Quantitative) Structure-Activity Relationship |
| RCR | Risk Characterization Ratio |
| RO | Reverse Osmosis |
| SAP | Sea Area For Calculating PEC |
| SOG | Speed Over Ground |

| | |
|----------|--|
| TDI | Tolerable Daily Intake |
| US EPA | The United States Environmental Protection Agency |
| WET | Whole Effluent Toxicity Test |
| WHO | World Health Organization |
| WHO/IPCS | World Health Organization/International Programme on Chemical Safety |

3 PRINCIPLES

3.1 The use of EGCS in the area to be assessed should not cause unacceptable risks, especially from a long-term perspective with respect to marine organisms, aquatic quality and/or human health, as assessed in accordance with these Guidelines.

4 APPLICATION

4.1 These Guidelines can be used by Member States when undertaking risk and impact assessments to ascertain whether EGCS discharge water can be discharged in their ports, harbours, estuaries, or coastal and other territorial waters.

4.2 The risk and impact assessments can be done at local, national or regional level (e.g. regional sea conventions) and be conducted at least in cooperation with neighbouring States. Alternatively, Member States can take into consideration risk and impact assessments undertaken by another Party.

5 GENERAL REQUIREMENTS

5.1 Targeted chemical substances and their data-set

5.1.1 The targeted chemical substances for environmental risk assessment (ERA)

5.1.1.1 The targeted chemical substances for ERA should at least include the following "priority hazardous substances":

- .1 cadmium;
- .2 lead;
- .3 mercury;
- .4 nickel;
- .5 vanadium;
- .6 chromium;
- .7 copper;
- .8 zinc;
- .9 acenaphthene;
- .10 acenaphthylene;
- .11 anthracene;
- .12 benzo(a)anthracene;
- .13 benzo(a)pyrene;
- .14 benzo(b)fluoranthene;
- .15 benzo(k)fluoranthene;
- .16 benzo(g,h,i)perylene;
- .17 chrysene;
- .18 fluoranthene;
- .19 fluorene;
- .20 indeno(1,2,3cd)pyrene;
- .21 naphthalene;

- .22 pyrene;
- .23 phenanthrene; and
- .24 dibenzo(a,h)anthracene.

5.1.1.2 The targeted chemical substances for ERA are not limited to the above priority hazardous substances. Other contaminants found in EGCS discharge waters may be added, taking into account the domestic regulations and specific factors from the sensitivity of the area to be assessed.

5.1.1.3 Also, for the area where the administration has concerns on eutrophication, relevant substances (e.g. nitrate, nitrite, ammonia and/or phosphate), which may dissolve into EGCS discharge waters, may be added.

5.1.2 Data-set for ERA

5.1.2.1 The Database of priority hazardous substances developed by the Organization, including physico-chemical data, ecotoxicological data and toxicological data, should be used for ERA.

5.1.2.2 Furthermore, the worst-case emission factors of the priority hazardous substances listed in paragraph 5.1.1.1 should be used for reasonable worst-case scenarios (see paragraph 6.2.2).

- .1 Emission Factors for the chemical substances are needed for ERA. In addition, the flow rate of the discharge water against exhaust flow may vary among EGCSs type and the load of engines connected to the EGCSs. However, such information does not depend on the location of the area to be assessed. Therefore, it is recommended that unified and representative Emission Factors (mg/MWh) based on the data for discharge water concentration and flow rate collected by the Organization be utilized.
- .2 If the Member States propose to use their original Emission Factors with a scientific reasoning based on their original measurement of EGCS discharge water, all the measurements should be analysed in accordance with the 2021 EGCS Guidelines.

5.1.2.3 The database will be placed to the IMO GISIS under a separate new item titled "Chemicals in EGCS Discharge Water".

5.1.2.4 For the targeted chemical substances for ERA, which are not included in the list of priority hazardous substances, the Member States should prepare the information as in paragraphs 5.1.2.1 and 5.1.2.2.

5.2 Information of the area to be assessed

5.2.1 Data stated in paragraph 5.2.2 should be collected by the Member States implementing the risk assessment in accordance with these guidelines.

5.2.2 Information of the area to be assessed

5.2.2.1 The following information of the area to be assessed is required:

- .1 geographical designation of the area to be assessed;

- .2 representative water and sediment quality of the area to be assessed;
- .3 the meteorographic/oceanographic information in table 1 on each Sea Area for calculating PECs (SAP);
- .4 existing threshold concentrations (PNEC, Predicted No Effect Concentration or EQS, Environmental Quality Standards) for each substance (in water, sediment and/or biota) indicating the level in the environment below which there should be no harm (lethal or sub-lethal) to the aquatic ecosystem or human health, taking account of the likely bioavailability of the substances where relevant; and
- .5 information on how chemical, biological and physical characteristics of the receiving environments, including their pH and salinity, could affect the level of risk.

Table 1: Parameters used for long-term environmental assessment

| Parameter | Unit | Remarks |
|------------------------------------|--------------------------------|--|
| Current | m/s | Representative value of each SAP. |
| Wind speed | m/s | Representative value of each SAP. |
| Wind direction | - | Consider the direction that affects the inflow to the mouth of each SAP. |
| Temperature | In Celsius | Annual average value of each SAP. |
| Salinity | PSU (Practical Salinity Unit)* | Representative value of each SAP. |
| pH | - | Representative value of each SAP. |
| Tidal difference | m | Representative value of each SAP. |
| Tidal period | hours | Representative value of each SAP. |
| Suspended particulate matter (SPM) | mg/L | Representative value of each SAP. |
| Depth of sediment layer | m | Representative value of each SAP. |
| Alkalinity | mg/l CaCO ₃ | Representative value of each SAP. |

* PSU \approx Salinity concentration in ppt (absolute salinity)

5.2.2.2 It is recommended that the information of the area to be assessed be collected by actual measurements, while representative values from literature can be used in case actual measurements are difficult. For parameters that change according to the season/time of the year, the changes of such parameters should be all-inclusively taken into account to ensure the representativeness of values.

6 RISK CHARACTERIZATION

6.1 Introduction

6.1.1 In this chapter, the methodology to assess the quantitative risks is described. Related international standards and/or existing guidance may be taken into account for risk characterization.

6.1.2 First, the daily loads (g/day) of all the chemical substances, which are discharged from EGCS, should be delivered based on the actual ship activities. Secondly, the PECs (ppt) of the chemical substances should be determined, taking into account the physico-chemical characteristics and the geographical and meteorographical/oceanographical conditions.

Also, the human exposure amount (g/kg-BW/day) may be delivered from the PECs. Finally, for risk characterization, the PEC and/or exposure amount, as predicted risk, is compared with the acceptance criteria. In general, if the ratios of PEC and PNEC, i.e. Risk Characterization Ratios (RCR) are less than 1, then the potential risks in the area to be assessed are acceptable. The cumulative effects of mixtures should be taken into account and a PEC/PNEC summation approach is recommended where PEC/PNEC ratios of all mixture components (PAHs and metals) are summed up to a final Risk Quotient. In addition, the Whole Effluent Toxicity testing may also be used to assess the cumulative effects of the targeted substances.

6.2 Emission scenarios

6.2.1 Activities

6.2.1.1 The actual activities (in total power output) of all ships operating in the SAP should be estimated, using received AIS data by satellites and/or local stations. The same methods described in the Fourth IMO GHG Study 2020 should be applied to calculate the hourly outputs of the main engine as kWh for each ship when operating in the SAP, using the information of SOG in the AIS signal. More simplified methodology may be used, such as utilising the averaged fuel consumption by ship types and sizes reported in the study and adjusting them by applying power curve between the actual power needed and speed obtained from AIS data.

6.2.1.2 The activities should include the power consumed in the auxiliary engines with the assumption that those would be all connected to EGCS, as far as corresponding data is available. To estimate the activities when the ships are stopped (mooring loading or unloading), relevant data from the ship or statistic data of ships³ should be used to assume the hourly outputs of the auxiliary engines as kWh for each ship when actual ship data is not available. Use of shore power or compliant fuel should be accounted for and excluded.

6.2.2 Reasonable worst-case scenarios

6.2.2.1 For Reasonable worst-case scenarios, the following assumptions should be applied:

- .1 the maximum ratio of ships using EGCS in the SAP should be set by the Member States, taking into account the current situation in the SAP and future increase;
- .2 all EGCSs installed onboard will be operated under open-loop operation, unless information to the contrary is available; and
- .3 the increase of the numbers of ships may be assumed taking into account the future growth of transportation amount and possible infrastructure expansion, as far as corresponding data is available.

6.2.3 The load of the targeted substances in discharge water

6.2.3.1 By multiplying the emission factors to the total activities, the load of each targeted substance in discharge water will be provided (g/day as the input for MAMPEC calculations).

³ Annex G to the Fourth IMO GHG Study 2020 shows auxiliary engine and boiler power demand assumptions in KW.

6.3 Exposure assessment for PEC

6.3.1 Introduction

6.3.1.1 To assess the risk of EGCS discharge water, in principle, the worst PEC in the area to be assessed should be identified. However, when designating a wide area to be assessed with complex geographical conditions, it may be difficult to simulate the total area with a single SAP with simplified assumption. In this case, multiple SAPs may be set, and PECs should be estimated for all SAPs.

6.3.1.2 It should be noted that PECs from the long-term viewpoint should be estimated. The tools for PECs should be appropriately selected for the purpose or time scale (the exposure time experienced by an organism) of PNEC, DNEL and/or DMEL.

6.3.2 Tools for long-term PEC of substances

6.3.2.1 The environmental concentrations of each substance after 10 years should be predicted using MAMPEC (see appendix 1). The MAMPEC model can take into account the fate of pollutants (e.g. accumulation and persistency) when predicting the concentrations that may be influenced by the hydrodynamical properties of local situations.

6.3.2.2 Although MAMPEC provides default geographical parameters for each "typical" marine environment (e.g. open sea, shipping lane, estuary, commercial harbour, yachting marina and open harbour), the actual geographical parameters collected for each SAP should be applied. Also, if the SAP(s) are too complicated to apply MAMPEC because of complex geography and/or more discharge points than MAMPEC model allows, the other simulation using 3D CFD may be used.

6.3.2.3 As a first assessment, the maximum value in the surroundings from the MAMPEC-BW calculations (e.g. the maximum PEC in the surroundings area outside the harbour. See section 6.8 of the MAMPEC 3.1 HANDBOOK) should be used as a representative concentration. If the result of the first assessment indicates potential risks comparing with the acceptance criteria, the average value from the MAMPEC-BW calculations may be used.

6.3.2.4 When calculating PECs in the SAP(s), the background concentrations of chemical substances should be added.

6.3.3 Selection of SAP for long-term calculation

6.3.3.1 It is recommended that SAP(s) for long-term calculation using a representative area in the area to be assessed including consideration of highest-risk area where the pollutants tend to accumulate, taking into account the geography, oceanic currents and tides, and/or the area with a higher traffic density compared to other areas.

6.3.3.2 To avoid insufficient risk assessment, an SAP should not be too small compared to the area to be assessed, and all SAPs for long-term calculation should, at least, cover the size of typical marinas. In addition, to ensure that SAPs appropriately represent the area to be assessed, SAPs for long-term calculation should cover a large part of the area to be assessed. Though SAPs for long-term calculation will be selected by the Member States, taking into account geographical conditions, in case of simple shape of the area to be assessed, it is recommended that the total SAP(s) cover more than 50% of the area to be assessed or that the ship activities in the total SAP(s) are more than 50% of those in the area to be assessed. The risk assessment for at least half of the area or the ship activities would prevent the arbitrary consequences of the assessment that result from specific small SAP(s).

6.4 Human exposure scenarios

6.4.1 Exposure scenarios involving the general public

6.4.1.1 In addition to the PECs of the targeted chemical substances, the human exposure amount of these substances may be assessed by applying exposure scenarios.

6.4.1.2 Exposure may occur indirectly, as is the case for the general public who may swim in water in areas where EGCS discharge water has been discharged, who eat seafood that has been caught in (the vicinity of) a discharge area, and/or who drink water prepared from the receiving water that may have been exposed to the EGCS discharge water. The following situations have been identified as probable exposure scenarios for the general public. It is recognized that there will be situations when the risk of human exposure is greater, such as amongst subsistence harvesters, and in these instances additional consideration should be given. Each exposure scenario should take into account concentrations in the water (PECs) estimated, as described in paragraph 6.3:

- .1 recreational activities in the sea (swimming);
- .2 eating seafood exposed to EGCS discharge water; and
- .3 drinking water prepared from receiving water that may have been contaminated by the EGCS discharge water.

6.4.1.3 For each scenario, exposure amount may be calculated based on the PEC. An aggregated exposure approach may be applied (see appendix 2).

6.5 Risk assessment

6.5.1 Introduction

6.5.1.1 Prior to the comparison between exposure levels and acceptance criteria, screening on PBT and CMR for each targeted chemical substance should be performed. The ratio of the estimated exposure to the acceptance criteria defines the risk assessment quotient: PEC/PNEC for the aquatic quality and aquatic organism and/or exposure/DNEL or exposure/DMEL for the human health risk assessment.

6.5.1.2 In addition to the PEC/PNEC ratio approach, a whole effluent assessment taking into account the EGCS discharge water may be performed. More details are stated in paragraph 6.7.

6.5.2 Environmental risk assessment

6.5.2.1 Screening for potential Persistence (i.e. poor degradation in the environment), Bioaccumulation (i.e. accumulation in organisms and food chains) and Toxicity (PBT) are necessary, taking into account the following elements:

- .1 Persistence:

Persistence should preferably be assessed in simulation test systems that determine the half-life under relevant conditions. Biodegradation screening tests may be used to show that the substances are readily biodegradable.

2.1.2 Guidance values for the general public (threshold effects)

Guidance values based on epidemiological studies, when available, are always preferred (WHO, 2000), and may be retrieved from internationally recognized bodies. These include guidance values established by, for example, JECFA or EFSA for food contaminants, such as TDI, and by WHO for chemicals in drinking water.

Guideline values for chemicals in drinking-water have been established for chemicals that cause adverse health effects after prolonged periods of time. A guideline value normally represents the concentration of a chemical that does not result in any significant risk to health over a lifetime of consumption. The guideline values assume a water consumption of 2 litres per day, and a body weight of 60 kg.

A number of provisional guideline values have, however, been established based on the practical level of treatment performance or analytical achievability. In these cases, the guideline value is higher than the calculated health-based value.

Table 1: Summary of examples of guidance values used for the general public

| Type of outcome | Term (units) | Abbreviation | Definition |
|--|---|--------------|---|
| Non-cancer, including laboratory animal carcinogens not relevant to humans | Tolerable daily intake (mg/kg bw/day) | TDI | An estimate of the amount of a substance in air, food, soil or drinking-water that can be taken in daily, weekly or monthly per unit body weight over a lifetime without appreciable health risk. |
| | Provisional tolerable weekly intake (mg/kg bw/week) | PTWI | |
| | Provisional tolerable monthly intake (mg/kg bw/month) | PTMI | |
| | Derived No Effect Level (mg/kg bw/day) | DNEL | |

2.1.3 Guidance values for the general public (non-threshold effects)

2.1.3.1 Approaches to risk assessment

Carcinogens can have a threshold or non-threshold mode of action. As a general rule, a risk for the general public from secondary exposure to a non-threshold carcinogenic substance is unacceptable. When it comes to the threshold carcinogens, these can be assessed by using a DNEL approach. In the case of the non-threshold carcinogens (i.e. with mutagenic potential), a different approach to risk assessment is recommended. In this guideline, the lifetime excess cancer risk level of 10^{-5} is used where possible (in accordance with the WHO Drinking Water Methodology, (WHO, 2001)).

2.1.3.2 Derived Minimal Effect Level

Calculation of an exposure level corresponding to a defined low risk, a Derived Minimal Effect Level (DMEL) is possible based on a semi quantitative approach. In contrast to a DNEL, a DMEL does not represent a "safe" level of exposure. It is a risk related reference value that could be used to better target risk management measures.

2.1.3.3 The large assessment factor approach

The "large assessment factor" approach results in DMEL values represents a low concern from a public health point of view. The basis for this assessment factor is that for substances that are both genotoxic and carcinogenic, an MOE of 10,000 or higher, based on a BMDL₁₀ from an animal study, is regarded to be of low concern (EFSA, 2017).

When a $BMDL_{10}$ from an animal study (oral rat carcinogenicity study) is used the assessment factors shown in table 2 should be used.

Table 2: Default assessment factors in the "large assessment factor approach" (modified from ECHA, 2012)

| Assessment factor | Default value systemic tumours |
|------------------------------------|--------------------------------|
| Interspecies | 10 |
| Intraspecies | 10 |
| Nature of the carcinogenic process | 10 |
| The point of comparison | 10 |
| Total assessment factor | 10,000 |

$$DMEL = \frac{BMDL_{10}}{\text{total assessment factor}} \quad (\text{Equation 1})$$

A DMEL derived according to this approach represents an excess cancer risk of 10^{-5} .

2.1.3.4 The slope factor approach

A slope factor is an estimate of the life-time cancer risk associated with a unit dose of a chemical through ingestion (or inhalation). The slope factor is defined as increased cancer risk from lifetime exposure to a substance by ingestion (or inhalation). It is expressed as an estimate of cancer risk associated with a unit concentration (mg/kg bw/d) or risk per mg/kg bw/d (US EPA, 2005). The slope factor may be used to derive the dose (mg/kg bw/d) associated with cancer at a specified risk level, for instance 10^{-5} (or 1 in 100 000). This dose may then be used as a DMEL.

2.1.3.5 Drinking-water guideline values

Drinking-water guideline values are normally determined using a mathematical model (the linearised multistage model) for chemicals considered to be genotoxic carcinogens. These guideline values are presented as concentrations in drinking-water associated with an estimated upper-bound excess lifetime cancer risk of 10^{-5} .

2.2 Exposure assessment

2.2.1 How and where humans may be exposed to EGCS discharge water

Humans may be exposed to EGCS discharge water when swimming in the water where the EGCS discharge water has been discharged, or when consuming seafood that has been caught in the vicinity of the area where the EGCS discharge water has been discharged. In some areas of the world, desalinated seawater is used as drinking water which will add another way of probable exposure. In this guideline, the aggregate exposure approach, as defined by WHO/IPCS (WHO/IPCS, 2009), is applied, that is the combined exposure applicable to each scenario. The term "aggregated exposure" (or "combined exposure"), as defined by the WHO/IPCS, takes into account all relevant pathways (e.g. food, water and residential uses) as well as all relevant routes (oral, dermal and inhalation).

2.2.2 Human exposure scenario

The exposure assessment is carried out through an evaluation of different exposure scenarios. An exposure scenario is a set of information and/or assumptions that describes the situations associated with the potential exposure.

2.2.3 Situations in which the general public might be exposed to EGCS discharge water

2.2.3.1 Exposure scenarios for the general public

Indirect exposure of humans via the environment associated with EGCS discharge water may occur by consumption of seafood and swimming in the receiving water. As a general principle, consumer exposure is normally assessed as being chronic and thus taking place throughout the whole lifetime in order to protect the most vulnerable population groups.

The following situations, as shown in table 3, have been identified as likely exposure scenarios for the general public, and have been regarded as a worst-case exposure.

As the human activities listed in table 3 are not performed near the discharge points for MAMPEC calculations, the maximum PECs in the surroundings should be used as representative concentration in a worst-case exposure.

Table 3: Summary of exposure scenarios for the general public

| Situations in which the general public may be exposed to EGCS discharge water containing chemicals | | |
|---|--|--|
| Situation | Exposure | Duration/quantity |
| Recreational activities in the sea | Inhalation of chemicals partitioning into the air above the sea | 2 events of 0.5 hours/day |
| | Dermal exposure to chemicals whilst swimming in the sea | 2 events of 0.5 hours/day |
| | Swallowing of seawater contaminated with EGCS discharge water | 2 events of 0.5 hours/day |
| Eating seafood exposed to EGCS discharge water | Oral consumption | Once or twice/day equivalent to 0.107 kg/day |
| Drinking water prepared from receiving water that may have been contaminated by the EGCS discharge water | Inhalation of chemicals volatilising from drinking water while showering | 0.75 hours/day |
| | Dermal exposure to chemicals in drinking water while showering | 0.75 hours/day |
| | Ingestion exposure to chemicals in drinking water | Daily total drinking water intake of 2 L/day |
| Aggregated exposure (through swimming, consumption of seafood and using drinking water) | | |

A number of assumptions are being used in the human exposure scenarios for the general public. These assumptions are listed in table 4. In all scenarios, default parameters leading to worst-case assessment are applied. Accordingly, the body surface area of men is assumed, but the body weight of women (60 kg) is applied. The whole-body surface area for men is 1.94 m². One parameter, ingestion rate of water while swimming, is taken from the Swimodel (US EPA, 2003).

Table 4: Summary of physiological parameters in human exposure scenarios for the general public

| Parameter | Value | Reference |
|---|------------------------|--|
| Body weight | 60 kg | WHO (2017) |
| Whole body, surface area | 1.94 m ² | US EPA (1997) |
| Ventilation rate (light activity) | 1.25 m ³ /h | ECHA (2012) |
| Ingestion rate of water while swimming | 0.025 L/h | Swimodel, US EPA (2003) |
| Ingestion rate of drinking water | 2 L/d | WHO (2017) |
| Showering | 0.75 h/d | US EPA (2011) |
| Quantity of fish consumed | 0.107 kg/d | AIST, Japan (2007) |
| Temperature | 293 K | GESAMP assumption |
| Dilution factor, swimming | 100 | EUSES (2016) |
| Reduction rate of chemicals through the desalination process for making up drinking water | 10 | Average reduction rate of chemicals through the RO treatment: 90% (Smol, M. and Włodarczyk-Makuła, M., 2017) |

2.2.3.2 Recreational activities (swimming) in the sea

- .1 Inhalation of chemicals partitioning into the air above the sea
Exposure in this scenario is through inhalation of air above the sea while swimming. The concentration of chemicals in the air may be calculated while using the Henry's law constant as described below.

The worst concentration of chemicals in the air may theoretically be calculated using the Henry's law constant. This physical law states that, the mass of gas dissolved by a given volume of solvent, is proportional to the pressure of the gas with which it is in equilibrium. The relative constant quantifies the partitioning of chemicals between the aqueous phase and the gas phase such as rivers, lakes and seas with respect to the atmosphere (gas phase). While making use of the concentration in the water phase, the concentration in the air phase is calculated accordingly:

$$C_{air} = \frac{H}{R \cdot T} \cdot C_{water} \quad (\text{Equation 2})$$

where:

- C_{air} = concentration in air (mg/m³);
 H = Henry's law constant (Pa m³/mole);
 R = gas constant (8.314 Pa m³/mole K);
 T = absolute temperature (K) (default = 293 K); and
 C_{water} = concentration in the water, i.e. maximum PECMAMPEC in surroundings (µg/L).

The concentration in water is the maximum predicted environmental concentration (PEC) value in surroundings as calculated by MAMPEC, and taking into account a dilution factor of 100 (due to wind, turbulence and insufficient time for the chemical to reach equilibrium) (EUSES, 2016). The inhaled dose may be estimated using the equation below, while taking into account various assumptions (number of swims, etc.).

$$Dose_{Inh} = \frac{C_{air} \cdot VR \cdot n \cdot Dur_{swim} \cdot Bio_{inh} \cdot 1000}{BW} \quad (\text{Equation 3})$$

where:

$Dose_{Inh}$ = inhalation intake of chemical during swimming ($\mu\text{g}/\text{kg bw}/\text{d}$);
 C_{air} = concentration in air (mg/m^3);
 VR = ventilation rate – light activity assumed ($1.25 \text{ m}^3/\text{h}$);
 n = number of swims per day ($2/\text{d}$);
 Dur_{swim} = duration of each swim (0.5 h);
 Bio_{inh} = fraction of chemical absorbed through the lungs (default = 1); and
 BW = body weight (default = 60 kg).

.2 Dermal exposure to chemicals while swimming in the sea

Option 1.

Exposure in this scenario is via dermal uptake of chemicals when swimming and where the permeability coefficient (K_p) is known, using the following equation,

$$Dose_{der} = \frac{C_{water} \cdot K_p \cdot Dur_{swim} \cdot n \cdot A_{skin} \cdot Bio_{der} \cdot 1000}{BW} \quad (\text{Equation 4.1})$$

where:

$Dose_{der}$ = dermal uptake per day during swimming ($\mu\text{g}/\text{kg bw}/\text{d}$);
 C_{water} = concentration in the water, i.e. maximum PECMAMPEC in surroundings ($\mu\text{g}/\text{L}$);
 K_p = dermal permeability coefficient (cm/h);
 Dur_{swim} = duration of each swim (0.5 h);
 n = number of swims per day ($2/\text{d}$);
 A_{skin} = surface area of whole body being exposed to water (1.94 m^2);
 Bio_{der} = bioavailability for dermal intake (default = 1); and
 BW = body weight (60 kg).

Option 2

If the K_p value is unknown, the following equation may be used as a conservative approach (ECHA, 2016),

$$Dose_{Der} = \frac{C_{water} \cdot TH_{der} \cdot n \cdot A_{skin} \cdot Bio_{der} \cdot 1000}{BW} \quad (\text{Equation 4.2})$$

where:

$Dose_{Der}$ = dermal uptake per day during swimming ($\mu\text{g}/\text{kg bw}/\text{d}$);
 C_{water} = concentration in the water, i.e. maximum PECMAMPEC in surroundings ($\mu\text{g}/\text{L}$);
 TH_{der} = thickness of the product layer on the skin (0.0001 m);
 N = number of swims per day ($2/\text{d}$);
 A_{skin} = surface area of whole body being exposed to water (1.94 m^2);
 Bio_{der} = bioavailability for dermal intake (default = 1); and
 BW = body weight (default = 60 kg).

- .3 Swallowing of water contaminated with EGCS discharge water
The oral uptake via swimming is calculated according to the following:

$$Dose_{Oral} = \frac{C_{water} \cdot IR_{swim} \cdot n \cdot Dur_{swim} \cdot Bio_{oral}}{BW} \quad (\text{Equation 5})$$

where:

Dose_{Oral} = amount of chemical swallowed (µg/kg bw/d);
C_{water} = concentration in the water, i.e. maximum PECMAMPEC in surroundings (µg/L);
IR_{swim} = ingestion rate of water while swimming (0.025 L/h);
N = number of swims per day (2/d);
Dur_{swim} = duration of each swim (0.5 h);
Bio_{oral} = bioavailability for oral intake (default = 1); and
BW = body weight (default = 60 kg).

2.2.3.3 Eating seafood exposed to EGCS discharge water

The concentration of chemicals in the seafood that is being consumed is calculated in this way:

$$C_{fish} = BCF \cdot C_{water} \quad (\text{Equation 6})$$

where:

C_{fish} = concentration in fish (µg/kg);
BCF = bioconcentration factor (L/kg); and
C_{water} = concentration in the water, i.e. maximum PECMAMPEC in surroundings (µg/L).

The calculation of concentrations in seafood has to be carried out for all chemicals. The cut-off value for the bioconcentration factor as described for the environmental risk assessment (paragraph 6.6.3) is not applicable in the risk assessment for human health. Making the assumption that people in the area only consume fish that is being caught locally (worst-case scenario), the daily intake may be calculated in the following way:

$$Dose_{fish} = \frac{QFC \cdot C_{fish} \cdot Bio_{oral}}{BW} \quad (\text{Equation 7})$$

where:

Dose_{fish} = uptake of chemical from eating fish (µg/kg bw/d);
QFC = quantity of fish consumed/day (= 0.107 kg/d (AIST, Japan (2007)));
C_{fish} = maximum concentration of chemical in fish (µg/kg);
Bio_{oral} = bioavailability for oral intake (default = 1); and
BW = body weight (default = 60 kg).

2.2.3.4 Drinking water made from receiving water that may have been contaminated by EGCS discharge water:

- .1 Inhalation of chemicals volatilisation from drinking water while showering

Exposure in this scenario is through inhalation of chemicals volatilising from drinking water while showering. The concentration of chemicals in the air may be calculated while using the Henry's law constant as already described in equation 1. The concentration in the drinking water is the same as in the scenario 2.2.3.2 and 2.2.3.3, while also taking into consideration a removal ratio of 10 in Reverse Osmosis (RO) desalination process (Smol, M. and

Włodarczyk-Makula, M., 2017), based on the concentration in the receiving water (i.e. the maximum PECs in the surroundings of MAMPEC calculation).

$$C_{air} = \frac{H}{R \cdot T} \cdot C_{DW} \quad (\text{Equation 8})$$

where:

C_{air} = concentration in air (mg/m³);
 H = Henry's law constant (Pa m³/mole);
 R = gas constant (8.314 Pa m³/mole K);
 T = absolute temperature (K) (default = 293 K); and
 C_{DW} = concentration in the drinking water, i.e. maximum PECMAMPEC in surroundings (µg/L)·0.9 (µg/L).

The inhaled dose, while showering, may be estimated using the equation below, while taking into account various assumptions,

$$Dose_{Inh} = \frac{C_{air} \cdot VR \cdot n \cdot Dur_{show} \cdot Bio_{inh} \cdot 1000}{BW} \quad (\text{Equation 9})$$

where:

$Dose_{Inh}$ = inhalation intake of chemical while showering (µg/kg bw/d);
 C_{air} = concentration in air (mg/m³);
 VR = ventilation rate – light activity assumed (1.25 m³/h);
 N = number of showers per day (1/d);
 Dur_{show} = duration of each shower (0.75 h);
 Bio_{inh} = fraction of chemical absorbed through the lungs (default = 1); and
 BW = body weight (default = 60 kg).

.2 Dermal exposure to chemicals while showering

Option 1

Exposure in this scenario is via dermal uptake of chemicals when taking a shower, and where the dermal permeability coefficient (K_p) is known, is calculated using the following equation,

$$Dose_{der} = \frac{C_{DW} \cdot K_p \cdot Dur_{show} \cdot n \cdot A_{skin} \cdot Bio_{der} \cdot 1000}{BW} \quad (\text{Equation 10.1})$$

where:

$Dose_{der}$ = dermal uptake per day during showering (µg/kg bw/d);
 C_{DW} = concentration in the drinking water, i.e. maximum PECMAMPEC in surroundings (µg/L)·0.9 (µg/L);
 K_p = dermal permeability coefficient (cm/h);
 Dur_{show} = duration of each shower (0.75 h);
 N = number of showers per day (1/d);
 A_{skin} = surface area of whole body being exposed to water (1.94 m²);
 Bio_{der} = bioavailability for dermal intake (default = 1); and
 BW = body weight (60 kg).

Option 2

If the K_p value is unknown, the following equation may be used as a conservative approach,

$$Dose_{Der} = \frac{C_{DW} \cdot TH_{der} \cdot n \cdot A_{skin} \cdot Bio_{der} \cdot 1000}{BW} \quad (\text{Equation 10.2})$$

where:

$Dose_{Der}$ = dermal uptake per day during showering ($\mu\text{g}/\text{kg}$ bw/d);
 C_{DW} = concentration in the drinking water, i.e. maximum PECMAMPEC in surroundings ($\mu\text{g}/\text{L}$) \cdot 0.9 ($\mu\text{g}/\text{L}$);
 TH_{der} = thickness of the product layer on the skin (0.0001 m);
 N = number of showers per day (1/d);
 A_{skin} = surface area of whole body being exposed to water (1.94 m²);
 Bio_{der} = bioavailability for dermal intake (default = 1); and
 BW = body weight (default = 60 kg).

.3 Ingestion exposure to chemicals in drinking water

The oral uptake via drinking water is calculated according to the following,

$$Dose_{Oral} = \frac{C_{DW} \cdot IR_{drink} \cdot Bio_{oral}}{BW} \quad (\text{Equation 11})$$

where:

$Dose_{Oral}$ = amount of chemical swallowed ($\mu\text{g}/\text{kg}$ bw/d);
 C_{DW} = concentration in the drinking water. i.e. maximum PECMAMPEC in surroundings ($\mu\text{g}/\text{L}$) \cdot 0.9 ($\mu\text{g}/\text{L}$);
 IR_{drink} = ingestion rate of drinking water (2 L/d);
 Bio_{oral} = bioavailability for oral intake (default = 1); and
 BW = body weight (default = 60 kg).

2.2.4 Concluding remarks

It should be noted that while the above situations have been identified as typical worst-case exposure scenarios, it is recognized that there will be other situations when exposure of the general public may be greater or less, and consideration should be given to such situations. In addition, the consumer exposure (general public) is normally assessed as chronic/lifetime risk in order to protect the most vulnerable population groups.

2.3 Risk characterization and acceptance criteria

2.3.1 General approach

The Risk Characterization Ratios (RCR) compares the exposure estimates to various DNELs or DMELs. The RCR is calculated according to the following formulae:

$$RCR = \frac{Exposure}{DNEL} \quad (\text{Equation 12})$$

or

$$RCR = \frac{Exposure}{DMEL} \quad \text{(Equation 13)}$$

In both cases, RCR should be used as acceptance criteria. If the $RCR < 1$, the exposure will lead to no unacceptable risk. However, risks are regarded to be controlled when the estimated exposure levels exceed the DNEL and/or the DMEL, that is, if the $RCR \geq 1$.

2.3.2 Health risks for the general public

In the three scenarios applicable for the general public, swimming in seawater contaminated with EGCS discharge water, ingestion of seafood which has been exposed to EGCS discharge water and ingestion of drinking water prepared from receiving water that may have been contaminated by the EGCS discharge water, are taken into consideration.

Aggregated exposure (through swimming, consumption of seafood and drinking water prepared from receiving water that may have been contaminated by the EGCS discharge water), that is the combined exposure applicable to each scenario, is estimated.

The total amount of chemicals that is absorbed as a result of the exposure to the general public, whilst swimming in the sea, eating fish and being exposed to drinking water through showering and drinking water consumption, may be summarised as in table 5.

Table 5: General public scenario – DNEL approach

| Chemical Name | Scenario ($\mu\text{g}/\text{kg bw}/\text{d}$) | | | | | | | Aggregated exposure ($\mu\text{g}/\text{kg bw}/\text{d}$) | DNEL ($\mu\text{g}/\text{kg bw}/\text{d}$) | RCR |
|---------------|--|--------|------|------------------------|----------------|--------|------|---|--|-----|
| | Swimming | | | Consumption of seafood | Drinking water | | | | | |
| | Inhalation | Dermal | Oral | Oral | Inhalation | Dermal | Oral | | | |
| A | | | | | | | | | | |
| B | | | | | | | | | | |
| C | | | | | | | | | | |

The risk-related reference value (DMEL) may be used to calculate an indicative RCR regarding potential cancer risk. DMELs can be used to estimate a risk dose based on the probability of increased cancer incidence over a lifetime (10^{-5}) for the general public (table 6).

Table 6: General public scenario – DMEL approach

| Chemical name | Aggregated exposure ($\mu\text{g}/\text{kg bw}/\text{d}$) | DMEL ($\mu\text{g}/\text{kg bw}/\text{d}$) | Indicative RCR |
|---------------|---|--|----------------|
| A | | | |
| B | | | |
| C | | | |

2.3.3 Mixture toxicity (including dose addition approach)

EGCS discharge water frequently contains mixtures of several chemicals which lead similar mechanism in human systems. One possible way to deal with this situation is to adopt an established international risk assessment approach (known as "grouping" or "dose addition"; Kortenkamp, et al., 2009), which entails a summation of the Risk Characterization Ratios (RCRs) of all substances with recognized carcinogenic potential. This approach had, for example, been used previously for carcinogens by the US EPA (US EPA, 1989), where it is based on the assumption that for carcinogens no dose threshold exists, and that the dose-response function is therefore essentially linear. Thus, if the EGCS discharge water

contains two or more chemicals with the same toxicological effect, these could be evaluated as an "assessment group". The RCR for an assessment group is calculated by the addition of all RCRs of the individual components,

$$RCR_{group} = RCR_A + RCR_B + RCR_C + \dots + RCR_n \quad (\text{Equation 14})$$

where:

RCR_n = the Risk Characterization Ratios shown in table 5 or table 6.

For the group RCR, the same conclusions apply as described above, that is, if the RCR < 1 using the RCRs in table 6, the exposure is deemed to represent no unacceptable risk. If still an unacceptable risk is identified, further refinement of the exposure assessment and/or the assessment factors might be performed giving special attention to route-specific contributions and additional RMM.

References

AIST (2007). Japanese Exposure Factors Handbook. National Institute of Advanced Industrial Science and Technology.

ECHA (2012). Guidance on information requirements and chemical safety assessment. Chapter R.8: Characterisation of dose (concentration)-response for human health. Version 2.1 November 2012.

ECHA (2016). Guidance on Information Requirements and Chemical Safety Assessment. Chapter R.15: Consumer exposure assessment. Version 3.0 July 2016.

EFSA (2017). Guidance. Update: use of the benchmark dose approach in risk assessment. EFSA Journal, 15 (1), 4658.

EUSES (2016). The European Union System for the Evaluation of Substances (EUSES). Version 2.1. European Chemicals Agency (ECHA), 2016.

Kortenkamp, A.; Backhaus, T.; and Faust, M. (2009). State of the art report on mixture toxicity. Final report.

Smol, M.; and Włodarczyk-Makuła, M. (2017). The effectiveness in the removal of PAHs from aqueous solutions in physical and chemical processes: a review. Polycyclic Aromatic Compounds, 37(4), 292-313.

US EPA (1989). Risk Assessment – Guidance for superfund. Vol 1. Human Health Evaluation Manual. Part A.

US EPA (1997). Exposure Factors Handbook Vol. I-III. (Update to Exposure Factors Handbook EPA/600/8-89/043 – May 1989). US Environmental Protection Agency (EPA), Office of Research and Development, EPA/600/P-95/002Fa, Washington, DC.

US EPA (2003). User's Manual Swimmer Exposure Assessment Model (SWIMODEL) Version 3.0. US EPA, Office of Pesticide Programs, Antimicrobials Division, November 2003.

US EPA (2005). Guidelines for Carcinogen Risk Assessment. Available at: https://www.epa.gov/sites/production/files/2013-09/documents/cancer_guidelines_final_3-25-05.pdf

US EPA (2011). Exposure Factors Handbook: 2011 Edition. US Environmental Protection Agency (EPA), Office of Research and Development, EPA/600/R-09/052F, Washington, DC.

US EPA (2012). Benchmark Dose Technical Guidance. Risk Assessment Forum, US Environmental Protection Agency (EPA), EPA/100/R-12/001, Washington, DC.

WHO (2000). Working Group report on Evaluation and use of epidemiological evidence for environmental health risk assessment: WHO Guideline Document Environmental Health Perspective, 108, 997-1002.

WHO (2001). Water Quality Guidelines, Standards and Health Assessment of risk and risk management for water-related infectious disease. Fewtrell, L. and Bartram, J. (Eds)

WHO/IPCS (2009). Harmonisation Project Document 7. Assessment of combined exposures to multiple chemicals: report of a WHO/IPCS international workshop on aggregate/cumulative risk assessment.

WHO (2017). Guidelines for drinking-water quality, 4th edition, incorporating the 1st addendum.
