
RULES FOR THE SURVEY AND CONSTRUCTION OF SHIPS OF FIBREGLASS REINFORCED PLASTICS

RULES

2010 AMENDMENT NO.1

Rule No.91 15th October 2010

Resolved by Technical Committee on 6th July 2010

Approved by Board of Directors on 27th July 2010

Rule No.91 15th October 2010

AMENDMENT TO THE RULES FOR THE SURVEY AND CONSTRUCTION OF SHIPS OF FIBREGLASS REINFORCED PLASTICS

“Rules for the survey and construction of ships of fibreglass reinforced plastics” has been partly amended as follows:

Chapter 2 CLASS SURVEYS

2.2 Classification Survey during Construction

2.2.1 General

Sub-paragraph -2 has been amended as follows.

2 ~~In principle, new~~ The new installation of materials which contain asbestos is to be prohibited.

2.2.3 Plans and Documents to be submitted for Reference

Sub-paragraph -1(6) has been deleted.

1 Where intended for the classification survey during construction, the following plans or documents are to be submitted for reference, in addition to those for approval required in **2.2.2**:

~~(6) Where materials which contain asbestos are used, documents including the location and other detailed information.~~

EFFECTIVE DATE AND APPLICATION

1. The effective date of the amendments is 1 January 2011.

GUIDANCE FOR THE SURVEY AND CONSTRUCTION OF SHIPS OF FIBREGLASS REINFORCED PLASTICS

GUIDANCE

2010 AMENDMENT NO.1

Notice No.100 15th October 2010

Resolved by Technical Committee on 6th July 2010

Notice No.100 15th October 2010

AMENDMENT TO THE GUIDANCE FOR THE SURVEY AND CONSTRUCTION OF SHIPS OF FIBREGLASS REINFORCED PLASTICS

“Guidance for the survey and construction of ships of fibreglass reinforced plastics” has been partly amended as follows:

Chapter 2 CLASS SURVEYS

Section 2.2 has been deleted.

~~2.2 Classification Survey during Construction~~

~~2.2.1 General~~

~~For the application of the requirements of 2.2.1.2 of the Rules, installation of materials which contain asbestos may be allowed where deemed as necessary by the Society in such positions as shown below;~~

- ~~(1) vanes used in rotary vane compressors and rotary vane vacuum pumps;~~
- ~~(2) watertight joints and linings used for the circulation of fluid when, at high temperature in excess of 350°C or pressure in excess of 7 MPa, there is a risk of fire, corrosion or toxicity; and~~
- ~~(3) supple and flexible thermal insulation assemblies used for temperatures above 1,000°C.~~

EFFECTIVE DATE AND APPLICATION

1. The effective date of the amendments is 1 January 2011.