

標題

パナマ籍船の非常脱出用呼吸具(EEBD)について

ClassNK

テクニカル インフォメーション

No. TEC-1157
発行日 2018年7月20日

各位

今般、パナマ政府は、非常脱出用呼吸具の特別要件についての解釈(Merchant Marine Circular No.142)を一部改正しましたので、以下のとおりお知らせ致します。

非常用脱出呼吸具

1. EEBD の数

- (1) 貨物船:居住区域に2組及び1組の予備。
- (2) 36人以下の旅客を運送する旅客船:各垂直区域に2組及び2組の予備。(SOLAS II-2/13.3.4.5規則で定義されるものを除く)
- (3) 36人を超える旅客を運送する旅客船:各垂直区域に4組及び2組の予備。(SOLAS II-2/13.3.4.5規則で定義されるものを除く)
- (4) 乗組員が通常または定期的に従事するA類機関区域に次のとおりEEBDを備えること。
 - (i) 機関制御室が当該機関区域内に配置される場合、機関制御室に1組。
 - (ii) 工作室がある場合、工作室に1組。ただし、工作室から脱出経路に直接アクセスできる場合、工作室に対するEEBDを省略して差し支えない。
 - (iii) 各甲板または台甲板において、脱出経路となる脱出はしごの近くに1組(閉囲された脱出トランク及び機関区域下層の水密扉を除く。)
- (5) 2つ以上の甲板を持つ機関室には、各甲板の上記(4)(iii)の場所に1組。

2. 予備

船上に10組以下のEEBDを備える場合は上記1.の通り少なくとも1組の予備のEEBDを備えること。11組から20組のEEBDを備える場合は少なくとも2組の予備のEEBDを備えること。20組より多くEEBDを備える場合は要求されるEEBDの10%分の予備のEEBDを備えること。ただし、4組を超える予備のEEBDは要求されない。

3. 訓練用

居住区域及び機関区域に要求されるEEBD並びに予備のEEBDに加え、少なくとも1組の訓練用EEBDを備えること。ただし、訓練に使用されるEEBDのシリンダを再充填する装置を備える場合は、訓練用として新たにEEBDを備える必要はない。また、いずれの場合にあっても、訓練に使用されるEEBDのシリンダには"訓練用"と表示すること。

(次頁に続く)

NOTES:

- ClassNK テクニカル・インフォメーションは、あくまで最新情報の提供のみを目的として発行しています。
- ClassNK 及びその役員、職員、代理もしくは委託事業者のいずれも、掲載情報の正確性及びその情報の利用あるいは依存により発生する、いかなる損失及び費用についても責任は負いかねます。
- バックナンバーは ClassNK インターネット・ホームページ(URL: www.classnk.or.jp)においてご覧いただけます。

4. 上記要件は全てのパナマ籍船に適用されます。2018年5月1日以降の安全設備(Safety Equipment)の最初の定期的検査において弊会検査員が適合していることを確認します。配置の変更が必要な場合、船上の火災制御図の訂正が必要となりますのでご注意ください。

今号のClassNK テクニカル・インフォメーション発行をもちまして、先にお知らせしていました2018年5月2日付のClassNK テクニカル・インフォメーション No. TEC-1150を絶版とします。

なお、本件に関してご不明な点は、以下の部署にお問い合わせください。

一般財団法人 日本海事協会 (ClassNK)

本部 管理センター別館 材料艀装部

住所: 東京都千代田区紀尾井町 3-3(郵便番号 102-0094)

Tel.: 03-5226-2020

Fax: 03-5226-2057

E-mail: eqd@classnk.or.jp

添付:

1. Merchant Marine Circular No.142





PANAMA MARITIME AUTHORITY
MERCHANT MARINE CIRCULAR MMC-142

PanCanal Building
Albrook, Panama City
Republic of Panama
Tel: (507) 501-5355
mmc@amp.gob.pa

To: Ship-owners/Operators, of Panamanian Flagged Vessels, Class Societies and Recognized Organizations (RO's).

Subject: Emergency Escape Breathing Devices (EEBD)

Reference: a. SOLAS 74, 2000 amendments.
b. MSC/Circ.1081 – Unified interpretation of the revised SOLAS Chapter II-2 – 13 June 2003.
c. IMO MSC.1/Circ.849 – May 1998.

1 Purpose

This Merchant Marine Circular replaces MMC 119.

2 Application

The 2000 amendments to SOLAS 74, Chapter II-2, Reg. 13 require Emergency Escape Breathing Devices (EEBD) which will be used for escape from a compartment that has a hazardous atmosphere. The EEBD have become mandatory under the new amendments for all ships to which the safety equipment certificate is required. The application of EEBDs provisions onboard Panama flag ships shall be as follow:

3 Number of EEBDs

- a. At least two (2) EEBDs in accommodation spaces of cargo ships and one (1) spare EEBD. Applicable to new and existing ships.
- b. At least two (2) EEBDs per main vertical zone, and a total of two (2) spare EEBDs. Applicable to new and existing passenger ships carrying not more than 36 passengers.
- c. At least four (4) EEBDs per main vertical zone, and a total of two (2) spare EEBDs.. Applicable to new and existing passenger ships carrying more than 36 passengers.
- d. For the purpose of this requirement (based on UI MSC/Circ. 1081), the minimum number of EEBDs required on machinery spaces shall be as follows:
 - i. One (1) EEBD at the engine control room if located inside the machinery space;

Prepared by: Lawyer	Revised by: Compliance and Enforcement Deputy Chief	Approved by: Compliance and Enforcement Chief
Control N°: F-RIN-04-01	Versión: 06	Date: August 1, 2016
		Page 1 of 3

- ii. One (1) EEBD at the machine shop or work shop area. If there is, however, a direct access to an escape way from the workshop, an EEBD is not required; and
- iii. One (1) EEBD located near the escape ladder used a second means of escape from the machinery space.

If the ship has a machinery space with more than one deck, then one (1) EEBD for each deck shall be placed at the same area as in point (.3)

4 Additional Spares

Ships with ten or less EEBDs on board shall carry at least one (1) spare device as mentioned in item 3. Ships with 11 to 20 EEBDs on board shall carry at least two spare devices. Ships with more than 20 EEBDs on board shall carry spares equal to at least 10 % of the total EEBDs but no more than 4 spares will be required. Applicable to new and existing ships.

Additional to the above requirements, the EEBD shall have a service duration of at least 10 minutes. Also, the number and location of EEBDs and spares shall be indicated in the fire control plan.

For existing ships, the requirement is to be complied with by the first survey after 1 July 2002. For more reference, the 2000 amendments to SOLAS 74, Chapter II-2, Reg. 1.2.2 clarify the applicable requirements to existing ships.

The detailed technical standards for the EEBD are separately provided in a mandatory code called “The International Code for the Fire Safety System (FSS Code)” adopted simultaneously.

Note: “New ships” cited above means ships constructed on or after 1 July 2002 and “Existing ships” means ships constructed prior to that date.

Authorized Organizations are instructed to follow the above mentioned guidelines, before issuing the appropriate certificate.

5 Training (as per the IMO MSC.1/Circ.849 – May 1998)

Training in the use of the EEBD should be considered as a part of basic safety training .At least one EEBD training device shall be used for training purposes at first Safety Equipment survey on or after 1st May 2018. This cylinder device will be in addition to EEBDs required for the machinery and accommodation spaces unless onboard means of recharging breathing apparatus cylinders is provided. If the rechargeable means is provided on board no additional training cylinder will be necessary. One of the cylinders must be marked for training only.

Personnel should be trained to immediately don an EEBD prior to exiting a space when the atmosphere becomes life threatening. This is necessary due to the possibility of encountering smoke during escape. Such training should be accomplished by scheduling routine escape drills for crew members working in the engineering or machinery spaces.

An EEBD may also be used to escape from a machinery space due to an accidental release of a fixed CO2 system and can be carried by firefighters for the sole purpose of providing the device to personnel in need of emergency assistance.

June, 2018- Point 4, Point 5

March, 2018 – Point 4, Point 5

January, 2018 – Point 3 a), b) and c) amended as well as 3 d) ii); subtitle 4 amended, and point 5 “Training added” as per IMO MSC.1/Circ.849 – may, 1998.

Prepared by: Lawyer	Revised by: Compliance and Enforcement Deputy Chief	Approved by: Compliance and Enforcement Chief
Control N°: F-RIN-04-01	Versión: 06	Date: August 1, 2016
		Page 2 of 3

June, 2013
November 2005 (revised)
April 2002

Inquiries concerning the subject of this Circular or any request should be directed to:
SEGUMAR-Panama
Directorate General of Merchant Marine
Panama Maritime Authority

Phone: (507) 501-5348 / 5350
Fax: (507) 501-5363 / 5364
E-mail: rberrocal@segumar.com
deputychief@segumar.com



Prepared by: Lawyer	Revised by: Compliance and Enforcement Deputy Chief	Approved by: Compliance and Enforcement Chief
Control N°: F-RIN-04-01	Versión: 06	Date: August 1, 2016
		Page 3 of 3