標題

MEPC 82 の審議結果の紹介



No. TEC-1343 発行日 2025年1月7日

各位

2024年9月30日から10月4日に国際海事機関(IMO)第82回海洋環境保護委員会(MEPC82) が開催されました。

今般、IMOより MEPC 82 の議事録及び決議並びにサーキュラーが発行されたことから、次の通り同 会合の情報及び審議結果をお知らせいたします。

1. 温室効果ガス(GHG)関連

地球温暖化対策の観点から温室効果ガス(GHG)排出削減が世界的な課題となっている 中、国際海運からのGHG排出削減対策はIMOにて検討が進められており、IMOではこ れまでにエネルギー効率設計指標による規制(EEDI/EEXI)、船舶エネルギー効率管理計 画書(SEEMP)の所持、燃料消費実績報告制度(IMODCS)及び燃費実績(CII)格付け 制度が導入されています。また、2023年7月に開催されたMEPC 80では、IMOの掲げる GHG排出削減目標(下表)とGHG排出削減策の候補を盛り込んだ「IMOGHG削減戦略」 の改訂版が採択され、以降、国際海運としての目標達成を目指して関連する様々な議論が 行われています。

目標年	GHG 排出削減目標(2023 年版)
	• 輸送効率最低 40%改善(2008 年比)
2020 年	・ GHG 総排出量の最低 20% 削減(30% 削減を目指す)
2030 +	(2008 年比)
	・ゼロエミッション燃料等の最低 5% 普及(10% 普及を目指す)
● GHG 総排出量の最低 70% 削減(80% 削減を目指す)	
2040 平	(2008 年比)
2050年	・ 遅くとも 2050 年頃までに GHG ネット排出ゼロ

今回の MEPC 82 では、GHG 排出削減のための中期対策に関する議論に加えて、短期対策 (EEXI 関連規制及び CII 格付け制度)の検証や舶用燃料のライフサイクル GHG 強度に 関するガイドラインの実用化に向けた議論などが行われました。

(次頁に続く)

NOTES:

- ClassNK テクニカルインフォメーションは、あくまで最新情報の提供のみを目的として発行しています。
- ClassNK及びその役員、職員、代理もしくは委託事業者のいずれも、掲載情報の正確性及びその情報の利用あるいは依存により 発生する、いかなる損失及び費用についても責任は負いかねます。
- バックナンバーは ClassNK インターネット・ホームページ(URL: www.classnk.or.jp)においてご覧いただけます。

(1) GHG 排出削減のための中期対策

2023 年版 IMO GHG 削減戦略では、国際海運における GHG 排出削減目標を達成する ための中期対策として、燃料の単位エネルギー当たりの GHG 排出量(GHG 強度)を 段階的に規制する「技術的手法」と GHG 排出等に応じた課金及び還付を行う仕組み である「経済的手法」を組み合わせた中期対策案(Basket of measures)を検討するこ とが掲げられています。

中期対策については、2027年の発効を目指して次に示す通り作業を進めることが MEPC 80 にて合意されています。

田問	作業内容		
一切印	作来的谷		
2023-2024	中期対策案の各組み合わせについて国際海運及び各国に及ぼす影響の 評価(包括的影響評価)を実施し、具体的な中期対策案を最終化		
2025	中期対策案の承認及び採択		
2027	中期対策の発効		

前回の会合では、条約改正の枠組み案を示す文書(IMO net-zero framework)が合意され、同文書を用いて各国・業界団体に対して中期対策案の最終化に向けた議論を進めていくことが要請されていました。

また、包括的影響評価については、UNCTAD(国連貿易開発会議)などにより実施された包括的影響評価の報告書が今回の会合に提出され、報告結果を踏まえた中期対策 案の審議が行われることとなりました。

今回の会合では、IMO net-zero framework を基に中期対策の論点が条約改正案として 整理されましたが、中期対策案の最終化にまでは至りませんでした。依然として、ラ イフサイクルベースの GHG 排出量の算定方法や GHG 強度基準・課金額の設定水準、 課金等により得られた収入の管理・分配方法など、多くの項目が争点として残されて います。これらの争点の収束による中期対策の 2027 年の発効に向けて、今後も継続 して議論されることになりました。

包括的影響評価については、中期対策の実施が輸送コストの中でも特に食糧の輸送コ スト上昇に与える影響についての懸念が共有され、食糧安全保障の観点からも影響評 価を追加実施することが合意されました。

(2) GHG 排出削減のための短期対策の検証

IMO による GHG 排出削減のための短期対策として導入されている EEXI(就航船の エネルギー効率指標)規制及び CII 格付け制度は、2026 年 1 月 1 日までにその有効 性を評価し、検証しなければならないことが MARPOL 条約附属書 VI で規定されて います。

また、CII 格付け制度については、船舶の種類や運航形態による有利・不利等の懸念点 を解決すべく、各国・業界団体から数多くの提案文書が提出されており、短期対策の 検証の際にあわせて検討することとなっておりました。

今回の会合では、短期対策の検証に際し、利用可能なデータ及び各国・業界団体から の提案に対する初期評価が実施されるとともに、短期対策の課題やその解決策の候補、 検討の優先度等を取り纏めた今後の議論のベースとなる文書が作成され、通信部会及 び中間作業部会において引き続き検討が行われることとなりました。

(3) 舶用燃料のライフサイクル GHG 強度に関するガイドライン (LCA ガイドライン)の 実用化

船舶の脱炭素化に向けて今後普及が予想される水素やアンモニア、バイオマスを原料 とした燃料などの低/ゼロ炭素燃料については、それら燃料の製造や流通過程におい て排出される GHG にも関心が高まっています。また、メタン(CH4)や亜酸化窒素 (N2O)といった CO2 以外の GHG についても、地球温暖化に与える影響が大きいこ とから注目されています。

前回の会合では、MEPC 80 で採択された LCA ガイドラインの改正版が 2024 年版 LCA ガイドラインとして採択され、専門家による科学的レビューとアドバイスを求めるた めに、GESAMP(海洋環境保護の科学的側面に関する合同専門家グループ)に「舶用 燃料ライフサイクル GHG 強度に関する作業部会(GESAMP-LCA WG)」を新設する ことが合意されていました。

今回の会合では、GESAMP-LCA WG が各燃料の排出係数のデフォルト値を検討できるように、加盟国に対し GESAMP-LCA WG にデフォルト値を申請するよう要請しました。さらに、GESAMP-LCA WG が燃料の認証スキームを検討できるように、加盟国及び国際機関に対し MEPC に認証スキームの枠組みを提案するよう要請しました。

- (4) 燃料消費実績報告制度のデータ収集に関するガイダンス
 - 前回の会合にて、IMO DCS で報告が要求される、項目の修正及び追加を含む MARPOL 条約附属書 VI 付録 IX の改正が採択され、燃料を使用する機器ごとの合計燃料消費 量や、実際の貨物輸送量など、より詳細な項目を報告することが求められることとな りました。本条約改正は 2025 年 8 月 1 日に発効となりますが、2025 年 1 月 1 日より 早期適用することが旗国に推奨されています。

一方、IMO へ報告されるデータはカレンダー暦年ごとに集計されるため、本条約改正の発効日以前と以降で収集するデータの項目に差が生じる可能性が指摘されました。

今回の会合では、2025 年を通じて同じデータを報告するために、就航船に対して本 条約改正に基づくデータ収集を実質 2026 年 1 月 1 日から開始することを認めるガイ ダンスが採択されました。なお、本ガイダンスは、本条約改正の任意の早期適用を妨 げるものではないことが確認されています。本件に関する具体的な適用スケジュール や必要なお手続き等につきましては、弊会テクニカルインフォメーション TEC-1339 をご覧ください。

(添付 4: MEPC.1/Circ.913 参照)

(5) 第5次 IMO GHG スタディの検討開始

IMO では国際海運からの GHG 排出量などを推定するスタディが定期的に実施され ています。直近では、2020年に実施された第4次 IMO GHG スタディにおいて、2012 年から 2018年の排出量および運航量当たりの GHG 排出量などが纏められています。 ただし、これらの GHG 排出量はいずれも船上からの排出(Tank-to-Wake)のみ考慮 したものとなっています。

今回の会合の直前に開催された第 17 回 GHG 中間作業部会(ISWG-GHG 17)にて、 第 5 次 IMO GHG スタディの内容に関する検討が開始されました。審議においては、 国際海運の GHG 排出のベースラインとなる 2008 年における排出量だけでなく燃料 中の炭素濃度などを明確にすべきとの意見や、排出量は Well-to-Wake ベースで計算 すべきなどの多くのコメントが表明されました。

そのため、次回会合において、これらの意見やコメントを踏まえ、第5次 IMO GHG スタディの内容に関する詳細な検討を継続して進めることとなりました。

- 2. バラスト水管理条約関連
 - (1) 型式承認取得後のバラスト水処理装置の改造
 - バラスト水処理装置を船上に搭載後、BWM 条約 D-2 規則を満たさないケースなどが 散見されることから、バラスト水処理装置の改造やモデルの改良を行う事例が多く発 生しています。これらの改造や改良には、フィルターの除去だけでなく、UV 照射シ ステムの変更や活性物質注入量の変更を含みます。このような改造及び改良に伴い新 規の型式承認が必要かどうかについては旗国の判断が異なる場合が多いため、業界よ り統一すべきとの指摘がありました。

本会合においては、バラスト水処理装置内の具体的な構成要素を例示し、型式承認を 必要とするかを明確にした内容を含む、型式承認手続きに係るガイダンスの改訂版 (BWM.2/Circ.43/Rev.2)が採択されました。 (添付 2: BWM.2/Circ.43/Rev.2 参照)

(2) バラスト水管理条約の見直し MEPC 80 にて作業が開始されたバラスト水管理条約(BWM 条約)の見直し作業について、今回の会合ではその作業を任命されている通信部会の進捗の報告及び議場での対面議論が実施され、その後引続き MEPC 83 への報告に向けて作業が継続することとなりました。

BWM 条約が発効した 2017 年以降、同条約の履行状況を評価し条約要件の見直しを 検討するための経験蓄積期間(EBP, Experience Building Phase)が設けられており、 MEPC 80 にて優先改正事項を含む条約レビュー計画(CRP, Convention Review Plan) が採択されています。その後、見直されるべき条約要件の選定作業が通信部会によっ て実施され、前回の MEPC 81 にて、条約本文、BWMS コード、関連ガイドライン及 びガイダンスにおいて改正が必要となる事項のリストが合意されていました。

今回の会合では、主に以下の内容について対面議論が実施され、通信部会の作業を円 滑に進めるための共通理解および論点が整理されました。

- ・ メンテナンスに関わる基準
- ・ BWMS データログの標準化
- 型式承認試験における処理速度と定格処理容量の整理
- 殺傷確認試験における試験時間
- 試験水中の添加物濃度及び添加生物濃度
- 更新検査における殺滅性能確認のための試験方法

なお、活性物質による処理の際に発生する消毒生成物質を将来規制対象にする提案についてはその具体的内容が充分でないとして、通信部会における議論に含めないことになりました。

3. その他の審議事項

- (1) シップリサイクル条約
 - 船舶の解撤が安全かつ環境汚染を伴わない適切な管理下で実施されることを目的として、シップリサイクル条約(2009年の船舶の安全かつ環境上適正な再資源化のための香港国際条約)が2025年6月26日に発効する予定となっており、条約締約国を 旗国とする総トン数 500トン以上の船舶が適用対象となっています(弊会テクニカルインフォメーション TEC-1311参照)。一方で、1992年に発効したバーゼル条約 (及び1995年改正)では、有害廃棄物の廃棄を目的とした越境移動が原則禁止されています。

前回の会合では、シップリサイクル条約に適合する船舶であってもバーゼル条約によって最終航海を実施できない可能性について懸念が挙がり、両条約の相互関係性について検討することとなっていました。

今回の会合では、シップリサイクル条約とバーゼル条約の両条約の締約国に対して、 リサイクルする船舶にシップリサイクル条約の要件が適用され、条約に従って承認さ れた船舶リサイクル施設でリサイクルされる場合、バーゼル条約の規定が当該船舶の 越境移動に影響を及ぼしてはならないことをバーゼル条約事務局に通知することに ついて検討を求める暫定 IMO ガイダンスが採択されました。また、シップリサイク ル条約の履行について引続き情報共有に努めるよう各国及び IMO 事務局へ要請され ました。

(添付 3: HKSRC.2/Circ.1 参照)

- 採択された強制要件
 今回の会合で採択された主な強制要件は以下の通りです。
 - NOx 並びに SOx 及び PM 排出規制海域(ECA)の追加 カナダ北極海域及びノルウェー海海域を新たに NOx 並びに SOx 及び PM の ECA と して指定し、また IAPP 証書の追補の様式に船舶の建造日等に関連する詳細を追加す る MARPOL 条約附属書 VI の改正が採択されました。 (添付 1: 決議 MEPC.392(82)及び添付 5 参照)

発効日: 2026年3月1日

本改正により、2027年3月1日以降、これらの海域を航行する船舶に対して燃料油中の硫黄分濃度を0.10%に制限する SOx 及び PM 排出規制が適用されます。また、同海域を航行する以下の船舶に対して NOx 三次規制が適用されます。

NOx 三次規制の適用			
カナダ北極海 ECA	・2025年1月1日以降に起工又は同等の建造段階にある船舶		
ノルウェー海 ECA	 2026年3月1日以降に建造契約が行われる船舶 建造契約がない場合には、2026年9月1日以降に起工又は 同等の建造段階にある船舶 2030年3月1日以降に引渡しが行われる船舶 		

MEPC 82 の審議概要につきましては IMO ホームページにも掲載されていますのでご参照ください。 https://www.imo.org/en/MediaCentre/MeetingSummaries/Pages/MEPC-default.aspx

なお、本件に関してご不明な点は、以下の部署にお問い合わせください。

一般財団法人 日本海事協会 (ClassNK)
本部 管理センター別館 国際部
住所: 東京都千代田区紀尾井町 3-3(郵便番号 102-0094)
Tel.: 03-5226-2038
Fax: 03-5226-2734
E-mail: xad@classnk.or.jp

添付:

決議 MEPC.392(82):	Amendments to MARPOL Annex VI (Designation of the Canadian Arctic
	and the Norwegian Sea as Emission Control Areas for Nitrogen Oxides,
	Sulphur Oxides and Particulate Matter, as Appropriate)
BWM.2/Circ.43/Rev.2:	2024 Guidance for Administrations on the Type Approval Process for
	Ballast Water Management Systems
HKSRC.2/Circ.1:	Provisional Guidance on the Implementation of the Hong Kong and Basel
	Conventions with Respect to the Transboundary Movement of Ships
	Intended for Recycling
MEPC.1/Circ.913:	Guidance on the Application of the Amendments to Appendix IX of
	MARPOL Annex VI on Inclusion of Data on Transport Work and
	Enhanced Granularity in the IMO Ship Fuel Consumption Database (IMO
	DCS) as Adopted by Resolution MEPC.385(81)
	決議 MEPC.392(82): BWM.2/Circ.43/Rev.2: HKSRC.2/Circ.1: MEPC.1/Circ.913:

5. カナダ北極海及びノルウェー海 ECA の図示

ANNEX 1

RESOLUTION MEPC.392(82) (adopted on 4 October 2024)

AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO

Amendments to MARPOL Annex VI

(Designation of the Canadian Arctic and the Norwegian Sea as Emission Control Areas for Nitrogen Oxides, Sulphur Oxides and Particulate Matter, as appropriate)

THE MARINE ENVIRONMENT PROTECTION COMMITTEE,

RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,

RECALLING ALSO article 16 of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocols of 1978 and 1997 relating thereto (MARPOL), which specifies the amendment procedure and confers upon the appropriate body of the Organization the function of considering amendments thereto for adoption by the Parties,

HAVING CONSIDERED, at its eighty-second session, proposed amendments to MARPOL Annex VI concerning the designation of the Canadian Arctic and the Norwegian Sea as Emission Control Areas for Nitrogen Oxides, Sulphur Oxides and Particulate Matter, as appropriate, which were circulated in accordance with article 16(2)(a) of MARPOL,

1 ADOPTS, in accordance with article 16(2)(d) of MARPOL, amendments to MARPOL Annex VI, the text of which is set out in the annex to the present resolution;

2 DETERMINES, in accordance with articles 16(2)(f)(ii) and (iii) of MARPOL, that the amendments shall be deemed to have been accepted on 1 September 2025 unless prior to that date not less than one third of the Parties or Parties the combined merchant fleets of which constitute not less than 50% of the gross tonnage of the world's merchant fleet have communicated to the Organization their objection to the amendments;

3 INVITES the Parties to note that, in accordance with article 16(2)(g)(ii) of MARPOL, the said amendments shall enter into force on 1 March 2026 upon their acceptance in accordance with paragraph 2 above;

4 REQUESTS the Secretary-General, for the purposes of article 16(2)(e) of MARPOL, to transmit certified copies of the present resolution and the text of the amendments contained in the annex to all Parties to MARPOL;

5 ALSO REQUESTS the Secretary-General to transmit copies of the present resolution and its annex to Members of the Organization which are not Parties to MARPOL.

ANNEX

AMENDMENTS TO MARPOL ANNEX VI

(Designation of the Canadian Arctic and the Norwegian Sea as Emission Control Areas for Nitrogen Oxides, Sulphur Oxides and Particulate Matter, as appropriate)

ANNEX VI

REGULATIONS FOR THE PREVENTION OF AIR POLLUTION FROM SHIPS

Regulation 13

Nitrogen oxides (NO_x)

Tier III

- 1 A new sub-paragraph .3 is added to regulation 13.5.1.2 as follows:
 - ".3 1 March 2026 and is operating in the Norwegian Sea Emission Control Area. For the Norwegian Sea Emission Control Area, "ship constructed on or after 1 March 2026" means a ship:
 - .1 for which the building contract is placed on or after 1 March 2026; or
 - .2 in the absence of a building contract, the keel of which is laid or which is at a similar stage of construction on or after 1 September 2026; or
 - .3 the delivery of which is on or after 1 March 2030."
- 2 Between paragraphs 5.1.2 and 5.1.3, the word "when" is added.

3 At the end of regulation 13.5.1.3, "." is replaced with ":" and a new sub-paragraph .1 is added as follows:

".1 that ship is constructed on or after 1 January 2025 and is operating in the Canadian Arctic Emission Control Area."

Emission control area

4 At the end of sub-paragraph.3 of regulation 13.6, the word "and" is deleted and at the end of sub-paragraph .4, "." is replaced with ";".

5 New sub-paragraphs .5 and .6 are added to regulation 13.6 as follows:

- ".5 the Canadian Arctic Emission Control area, which means the area described by the coordinates provided in appendix VII to this Annex; and
- .6 the Norwegian Sea as defined in regulation 13.9.4 of Annex II of the present Convention."

Regulation 14

Sulphur oxides (SO_x) and particulate matter

Requirements within emission control areas

6 At the end of sub-paragraph .4 of regulation 14.3, the word "and" is deleted and, at the end of sub-paragraph .5, "." is replaced by ";".

- 7 New sub-paragraphs .6 and .7 of regulation 14.3 as follows:
 - ".6 the Canadian Arctic Emission Control area, which means the area described by the coordinates provided in appendix VII to this Annex; and
 - .7 the Norwegian Sea as defined in regulation 13.9.4 of Annex II of the present Convention."

Appendix I

Form of International Air Pollution Prevention (IAPP) Certificate (regulation 8)

SUPPLEMENT TO INTERNATIONAL AIR POLLUTION PREVENTION CERTIFICATE (IAPP CERTIFICATE)

RECORD OF CONSTRUCTION AND EQUIPMENT

7 Section 1.3 of the Supplement to the International Air Pollution Prevention Certificate is replaced by the following:

"1.3 Date of build

1.3.1 Date of building contract (*dd/mm/yyyy*)

1.3.2 Date on which keel was laid or ship was at a similar stage of construction (*dd/mm/yyyy*)

1.3.3 Date of delivery (dd/mm/yyyy)"

Appendix VII

Emission control areas (regulations 13.6 and 14.3)

8 Paragraph 1 is replaced by the following:

"1 The boundaries of emission control areas designated under regulations 13.6 and 14.3, other than the Baltic Sea, the North Sea, and the Norwegian Sea areas, are set forth in this appendix."

- 9 New paragraph 5 is added after paragraph 4 as follows:
 - "5 The Canadian Arctic area comprises two segments:

.1 starting at the Yukon mainland at 68°54'.00 N, 137°0'.00 W; following the coordinates listed below and ending at the north coast of Hans Island at 80°49'.91 N, 66°27'.40 W, connected by geodesic lines connecting the following coordinates in World Geodetic System 1984 (WGS84) datum:

POINT	LATITUDE	LONGITUDE
1	68°54'.00 N	137°0'.00 W
2	72°56'.58 N	137°0'.00 W
3	73°0'.42 N	136°21'.72 W
4	73°21'.72 N	136°20'.46 W
5	73°56'.34 N	136°57'.60 W
6	74°30'.18 N	137°13'.08 W
7	75°3'.42 N	137°7'.20 W
8	75°49'.26 N	136°32'.04 W
9	76°42'.18 N	136°57'.06 W
10	77°28'.26 N	136°34'.74 W
11	78°7'.26 N	135°28'.50 W
12	78°39'.72 N	133°44'.88 W
13	79°29'.58 N	131°24'.96 W
14	79°53'.16 N	129°32'.22 W
15	80°31'.44 N	127°33'.48 W
16	81°54'.36 N	118°36'.24 W
17	82°16'.32 N	116°28'.98 W
18	82°52'.86 N	115°29'.46 W
19	83°54'.54 N	112°7'.20 W
20	85°46'.14 N	97°16'.86 W
21	86°9'.78 N	89°14'.46 W
22	86°22'.56 N	78°59'.58 W
23	86°19'.18 N	60°10'.17 W
24	85°38'.92 N	58°10'.58 W
25	85°22'.29 N	57°59'.22 W
26	85°12'.04 N	57°54'.68 W
27	84°49'.56 N	57°13'.28 W
28	84°22'.15 N	56°43'.09 W
29	84°17'.32 N	56°35'.78 W
30	84°11'.05 N	56°29'.53 W
31	83°10'.79 N	57°0'.21 W
32	83°4'.29 N	57°27'.78 W
33	83°0'.95 N	57°32'.72 W
34	82°44'.71 N	58°0'.38 W
35	82°42'.57 N	58°6'.78 W
36	82°40'.69 N	58°11'.74 W
37	82°34'.95 N	58°25'.30 W
38	82°31'.25 N	58°38'.56 W
39	82°27'.52 N	58°50'.12 W

POINT	LATITUDE	LONGITUDE
40	82°22'.87 N	59°2'.00 W
41	82°20'.26 N	59°21'.38 W
42	82°18'.54 N	59°32'.25 W
43	82°17'.22 N	59°41'.31 W
44	82°14'.41 N	59°56'.06 W
45	82°12'.06 N	60°2'.23 W
46	81°51'.67 N	62°9'.60 W
47	81°17'.89 N	64°8'.73 W
48	80°50'.48 N	66°15'.33 W
49	80°50'.10 N	66°26'.97 W
50	80°49'.91 N	66°27'.40 W

.2 continuing from the south coast of Hans Island at 80°49'.29 N, 66°27'.04 W, following the coordinates listed below, and ending at the coast of Newfoundland and Labrador at 60°0'.00 N, 64°9'.60 W, connected by geodesic lines connecting the following coordinates in World Geodetic System 1984 (WGS84) datum:

POINT	LATITUDE	LONGITUDE
51	80°49'.29 N	66°27'.04 W
52	80°49'.19 N	66°26'.57 W
53	80°45'.43 N	67°3'.99 W
54	80°26'.16 N	68°14'.39 W
55	80°1'.79 N	68°46'.99 W
56	79°40'.38 N	69°4'.68 W
57	78°48'.09 N	72°52'.36 W
58	78°25'.05 N	73°45'.66 W
59	77°30'.83 N	74°38'.24 W
60	76°43'.47 N	74°56'.49 W
61	75°0'.00 N	73°16'.07 W
62	74°50'.67 N	73°2'.71 W
63	74°44'.20 N	72°52'.86 W
64	74°28'.67 N	71°45'.72 W
65	74°24'.02 N	71°25'.67 W
66	74°12'.42 N	70°33'.06 W
67	74°10'.03 N	70°23'.12 W
68	74°7'.50 N	70°12'.16 W
69	74°6'.15 N	70°6'.69 W
70	74°2'.53 N	69°51'.43 W
71	74°2'.25 N	69°50'.33 W
72	73°57'.54 N	69°31'.02 W
73	73°52'.27 N	69°10'.88 W
74	73°46'.73 N	68°51'.14 W
75	73°46'.17 N	68°48'.81 W

POINT	LATITUDE	LONGITUDE
76	73°41'.77 N	68°29'.65 W
77	73°37'.91 N	68°12'.34 W
78	73°36'.51 N	68°5'.42 W
79	73°31'.14 N	67°15'.52 W
80	73°25'.90 N	66°24'.99 W
81	73°18'.48 N	66°7'.91 W
82	72°50'.89 N	65°7'.52 W
83	72°47'.70 N	65°0'.63 W
84	72°45'.76 N	64°58'.22 W
85	72°43'.78 N	64°54'.27 W
86	72°36'.40 N	64°38'.74 W
87	72°30'.58 N	64°26'.04 W
88	72°24'.89 N	64°13'.11 W
89	72°10'.96 N	63°40'.55 W
90	72°6'.33 N	63°30'.42 W
91	72°1'.65 N	63°20'.73 W
92	71°52'.98 N	63°3'.86 W
93	71°47'.21 N	62°52'.67 W
94	71°44'.71 N	62°49'.41 W
95	71°32'.90 N	62°33'.35 W
96	71°31'.73 N	62°31'.66 W
97	71°29'.39 N	62°28'.99 W
98	71°25'.93 N	62°25'.37 W
99	71°18'.98 N	62°17'.45 W
100	71°12'.10 N	62°8'.98 W
101	70°51'.84 N	61°42'.53 W
102	70°48'.17 N	61°37'.62 W
103	70°35'.55 N	61°20'.28 W
104	70°33'.07 N	61°17'.10 W
105	70°13'.48 N	61°10'.49 W
106	70°8'.83 N	61°8'.67 W
107	70°7'.55 N	61°7'.92 W
108	70°1'.68 N	61°4'.08 W
109	69°55'.82 N	60°59'.85 W
110	69°55'.27 N	60°59'.41 W
111	69°49'.82 N	60°57'.99 W
112	69°29'.41 N	60°51'.36 W
113	69°12'.82 N	60°27'.40 W
114	69°10'.24 N	60°23'.47 W
115	69°6'.79 N	60°18'.33 W
116	69°0'.88 N	60°8'.99 W
117	68°56'.83 N	60°2'.21 W
118	68°38'.02 N	59°14'.43 W
119	68°37'.86 N	59°14'.01 W

POINT	LATITUDE	LONGITUDE	
120	68°34'.02 N	59°4'.46 W	
121	68°32'.88 N	59°1'.49 W	
122	68°25'.25 N	58°42'.06 W	
123	68°21'.67 N	58°38'.64 W	
124	68°16'.07 N	58°33'.75 W	
125	68°7'.40 N	58°26'.93 W	
126	68°6'.87 N	58°26'.58 W	
127	68°4'.26 N	58°24'.69 W	
128	68°1'.89 N	58°23'.15 W	
129	67°56'.94 N	58°19'.62 W	
130	67°44'.25 N	58°9'.79 W	
131	67°39'.77 N	58°6'.05 W	
132	67°35'.33 N	58°2'.07 W	
133	67°30'.76 N	57°57'.66 W	
134	67°29'.16 N	57°56'.00 W	
135	67°28'.21 N	57°55'.01 W	
136	67°27'.27 N	57°54'.57 W	
137	67°21'.52 N	57°52'.35 W	
138	66°49'.47 N	57°42'.84 W	
139	66°41'.71 N	57°40'.35 W	
140	66°37'.88 N	57°39'.45 W	
141	66°36'.02 N	57°38'.99 W	
142	66°30'.27 N	57°38'.04 W	
143	66°24'.50 N	57°37'.56 W	
144	66°18'.68 N	57°37'.55 W	
145	66°12'.84 N	57°38'.01 W	
146	66°3'.50 N	57°39'.45 W	
147	65°57'.62 N	57°39'.93 W	
148	65°57'.50 N	57°39'.93 W	
149	65°51'.75 N	57°40'.44 W	
150	65°50'.81 N	57°40'.46 W	
151	65°37'.59 N	57°41'.74 W	
152	65°34'.74 N	57°42'.18 W	
153	65°23'.33 N	57°44'.83 W	
154	65°18'.08 N	57°45'.70 W	
155	65°14'.52 N	57°44'.99 W	
156	65°11'.49 N	57°44'.22 W	
157	65°8'.79 N	57°43'.69 W	
158	65°6'.04 N	57°43'.95 W	
159	64°12'.06 N	57°48'.09 W	
160	64°4'.20 N	57°49'.01 W	
161	63°57'.36 N	57°53'.40 W	
162	63°52'.57 N	57°56'.46 W	
163	63°50'.05 N	57°57'.01 W	

POINT	LATITUDE	LONGITUDE
164	63°43'.99 N	57°58'.60 W
165	63°37'.16 N	58°1'.00 W
166	63°35'.02 N	58°1'.86 W
167	63°28'.62 N	57°59'.62 W
168	63°22'.86 N	57°57'.29 W
169	62°47'.14 N	57°40'.83 W
170	62°11'.35 N	57°25'.12 W
171	62°3'.47 N	57°22'.15 W
172	62°2'.23 N	57°21'.62 W
173	62°0'.39 N	57°20'.92 W
174	61°24'.74 N	57°16'.16 W
175	61°10'.14 N	57°38'.70 W
176	60°43'.56 N	57°17'.64 W
177	60°15'.36 N	57°4'.56 W
178	60°0'.00 N	56°43'.02 W
179	60°0'.00 N	64°9'.60 W



4 ALBERT EMBANKMENT LONDON SE1 7SR Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

> BWM.2/Circ.43/Rev.2 24 October 2024

F

INTERNATIONAL CONVENTION FOR THE CONTROL AND MANAGEMENT OF SHIPS' BALLAST WATER AND SEDIMENTS, 2004

2024 Guidance for Administrations on the type approval process for ballast water management systems

1 The Marine Environment Protection Committee (MEPC), at its sixty-first session (27 September to 1 October 2010), approved the *Guidance for Administrations on the type approval process for ballast water management systems in accordance with Guidelines (G8)*, developed by the Sub-Committee on Bulk Liquids and Gases (BLG) at its fourteenth session (8 to 12 February 2010), disseminated as BWM.2/Circ.28.

2 MEPC 65 (13 to 17 May 2013) approved amendments to the Guidance, developed by BLG 17 (4 to 8 February 2013), disseminated as BWM.2/Circ.43, superseding BWM.2/Circ.28.

3 MEPC 72 (9 to 13 April 2018) considered and approved a revision of the Guidance in order to reflect the requirements of the *Code for Approval of Ballast Water Management Systems* (resolution MEPC.300(72)).

4 MEPC 82 (30 September to 4 October 2024) considered and approved a revision of the Guidance to support harmonized evaluation by Administrations of modifications to a ballast water management system with existing type approval, as set out in the annex.

5 Member Governments and international organizations are invited to bring the annexed Guidance to the attention of all parties concerned.

6 This circular revokes BWM.2/Circ.28, BWM.2/Circ.43 and BWM.2/Circ.43/Rev.1.

NRVIGATING THE FUTURE: SAFETY FIRST!

ANNEX

2024 GUIDANCE FOR ADMINISTRATIONS ON THE TYPE APPROVAL PROCESS FOR BALLAST WATER MANAGEMENT SYSTEMS

1 PURPOSE

1.1 This document provides guidance for Administrations on the procedure for evaluating an application for type approval of a ballast water management system (BWMS), in accordance with the *Code for Approval of Ballast Water Management Systems* (BWMS Code)¹, or evaluating modifications to an existing type approved BWMS that are proposed by the manufacturer. The Guidance can act as an aide-memoire for Administrations and is not intended, in any way, to interfere with the authority of an Administration.

1.2 Modifications to an existing type approved BWMS may be to major components, as defined in the BWMS Code, or to minor components, as defined herein. Examples of major and minor components are provided in the appendix, tables 1 and 3, respectively. This document provides:

- .1 information to support a determination of the design and type of component that a BWMS manufacturer is proposing to modify (e.g. major or minor; refer to figure 1); and
- .2 procedural guidance to support an evaluation and approval of BWMS modifications.

1.3 For modifications to major components, Administrations should follow the BWMS Code and guidelines developed by the Organization to determine any associated testing requirements (for decision support see examples in table 2 in the appendix).

1.4 There is no requirement for existing BWMS installations with a valid Type Approval Certificate to be retroactively upgraded should a BWMS with an existing type approval obtain approval of modifications.

1.5 A BWMS originally type approved and installed taking into account Guidelines (G8) (i.e. resolutions MEPC.125(53), MEPC.174(58) and MEPC.279(70)), and before entry into effect of the BWMS Code, can undergo modifications to minor components following this guidance and does not require a shipowner or BWMS manufacturer to retroactively apply BWMS Code requirements to that installation.

1.6 This document provides guidance on interpretation of the BWMS Code and does not replace or supersede the requirements of the Code.

1.7 This document is intended to provide guidance to Administrations on the details of the type approval to be reported to the Committee.

¹ References to the BWMS Code are understood to refer to any revisions of the Code that may be in effect and applicable at the time of implementation of this Guidance by an Administration.

2 KEY INSTRUMENTS

In evaluating an application for type approval of a BWMS, or an application from a manufacturer for modification to a BWMS with an existing type approval, the latest version of the following instruments should be consulted:

- .1 International Convention for the Control and Management of Ships' Ballast Water and Sediments, 2004 (BWM Convention);
- .2 Procedure for approval of ballast water management systems that make use of Active Substances (G9) (resolution MEPC.169(57));
- .3 Guidelines for ballast water sampling (G2) (resolution (MEPC.173(58));
- .4 Code for Approval of Ballast Water Management Systems (resolution MEPC.300(72)) and Guidelines for approval of ballast water management systems (G8) (resolutions MEPC.125(53), MEPC.174(58) and MEPC.279(70)), as may be appropriate;
- .5 Guidance to ensure safe handling and storage of chemicals and preparations used to treat ballast water and the development of safety procedures for risks to the ship's crew resulting from the treatment process (BWM.2/Circ.20);
- .6 *Methodology for information gathering and conduct of work of the GESAMP-BWWG* (BWM.2/Circ.13, as revised); and
- .7 other pertinent ballast water management related resolutions, guidance and circulars.

3 RECOMMENDATIONS FOR REQUIREMENTS OF MANUFACTURERS OR THEIR AGENTS

3.1 To facilitate an initial or new type approval of a BWMS, the Administration should ensure that the manufacturers, or their agents have, at a minimum:

- .1 been informed if the Administration delegates to, or utilizes the services of, a third-party quality assurance organization (e.g. recognized organization, nominated body, classification society, surveyors, etc.) in some or all of the type approval processes;
- .2 understood the steps and requirements of the processes outlined in the instruments listed in section 2 of this Guidance;
- .3 a fully working system built that can be used in the type approval process. It should be noted that the construction procedures and materials for the unit tested need to be the same as for the follow-on production units;
- .4 undertaken preliminary testing to ensure that their BWMS is viable, will meet the D-2 standard of the BWM Convention, will work on board a ship and has been determined not to pose any unacceptable risk to the environment;
- .5 understood the extent of testing that needs to be completed by a recognized testing facility, including toxicity analysis;

- .6 provided a description of the preliminary test to the Administration that should at least include the following:
 - .1 the test set-up, including sampling points;
 - .2 responsible persons/organizations for all or portions of the preliminary testing;
 - .3 possible Quality Management Plan (QMP) of the testing facility;
 - .4 testing laboratories that will be used;
 - .5 Quality Assurance Project Plan (QAPP) for the preliminary test; and
 - .6 provision for survey of the test facility, if required;
- .7 provided a detailed report of the preliminary test results including, at least:
 - .1 toxicity data;
 - .2 Active Substances if relevant; and
 - .3 any Other Chemicals generated during the process;
- .8 an understanding of whether the system under consideration uses an Active Substance as defined in the BWM Convention. If it utilizes an Active Substance, the system will require additional approval under Procedure (G9), whilst the systems not using an Active Substance only need approval under the BWMS Code;
- .9 a contractual agreement to undertake the shipboard testing needed under the BWMS Code with the owner of a suitable ship;
- .10 arranged for a trained person from the land-based testing facility to operate the equipment being type approved and ensure that for the shipboard test the ship's crew is familiar with the equipment and sufficiently trained to operate the equipment;
- .11 consulted with the classification society that the ship undertaking the shipboard testing is being registered, where necessary, and obtained approval for installation of the BWMS;
- .12 demonstrated, by using mathematical modelling and/or calculations or by full-scale shipboard testing, that any up or down scaling will not affect the ultimate functioning and effectiveness on board a ship of the type and size for which the equipment will be certified. In doing so, the manufacturers should take into account all relevant guidelines developed by the Organization;
- .13 prepared a type approval application in compliance with the BWMS Code, annex, part 1, which includes at least the following:
 - .1 detailed description of the design, construction, operation and functioning of the BWMS;

- .2 a list of major components, as defined in the BWMS Code, that are included in the BWMS design (for decision support see examples in table 1 in the appendix);
- .3 preliminary assessment of the corrosion effects of the system proposed, if applicable;
- .4 preliminary test results;
- .5 technical manual;
- .6 BWMS piping and instrumentation diagram (P&ID);
- .7 link to the provisions required in a ballast water management plan;
- .8 environmental and public health effects;
- .9 specific salinities to be tested; and
- .10 a list of necessary measures for the safe operation of the BWMS;
- .14 provided the following, when submitting the type approval application:
 - .1 sufficient information to verify operation in different salinity ranges (fresh, brackish and marine water) in which the BWMS will operate;
 - .2 sufficient information to verify operation in the different temperature ranges (cold, temperate and tropical) in which the BWMS will operate;
 - .3 sufficient information to verify operation with the different sediment loads under which the BWMS will operate;
 - .4 sufficient information to verify operation of the minimum effective treatment flow rate as well as the maximum Treatment Rated Capacity (TRC) including the duration of these tests; and
 - .5 suggestions for improvements of the installation related to safety or additional testing R&D;
- .15 made all laboratory-scale and, if appropriate, full-scale land-based test results and documentation, including all unsuccessful, failed and invalid tests, available to the Administration; and
- .16 made all shipboard test results and documents, including all unsuccessful, failed and invalid tests, as well as detailed information of the test set up and flow rate at each test cycle, available to the Administration.

3.2 In accordance with paragraphs 4.17 to 4.22 of the *Code for Approval of Ballast Water Management Systems* (BWMS Code), Administrations should ensure that type-approved BWMS have a suitable self-monitoring system that will monitor and record sufficient data to verify correct operation of the system. Administrations should make every effort to ensure that newly installed BWMS that have already been granted type approval meet this recommendation within one year following approval of this Guidance. Administrations should issue treatment system particulars, including details of the self-monitoring system (as described in document MEPC 61/INF.19 and BWM.2/Circ.69, as may be revised), for all type-approved systems.

3.3 To facilitate an evaluation of modifications to a BWMS with an existing type approval, the Administration should ensure that the manufacturers or their agents have:

- .1 a BWMS with an existing type approval;
- .2 been informed if the Administration delegates to, or utilizes the services of, a third-party quality assurance organization (e.g. recognized organization, nominated body, classification society, surveyors, etc.) in some or all of the type approval processes;
- .3 received all relevant information to understand the steps and requirements of the processes outlined in the instruments listed in section 2 of this Guidance;
- .4 provided a clear description of the BWMS modifications and a technical description including the main characteristics of the current BWMS component(s), a comparative evaluation of the appropriateness of the new component(s), and all relevant documentation;
- .5 received all relevant information to understand which documents to submit for enabling the Administration to assess if the modification is a change to a major component in accordance with the definition in paragraph 3.9 of the BWMS Code;
- .6 for modifications to major components, received all relevant information to understand the extent of any testing that the Administration may require to be completed by an independent testing facility accepted by the Administration to allow full evaluation of the BWMS modification, including any analysis related to Final Approval taking into account Procedure (G9); and
- .7 made all reports of any required testing and documentation to support evaluation of the BWMS modification(s) available to the Administration.

4 **RECOMMENDATIONS FOR FACILITATING TYPE APPROVAL EVALUATION**

4.1 For those Administrations using third-party quality assurance organizations, due care should be taken to ensure all such arrangements are in place prior to initiating the type approval programme.

4.2 The Administration should provide the applicant with a document outlining contact details, the expected amount of time between submission and decision and any other requirements separate from the procedures and requirements outlined in the instruments listed in section 2 of this Guidance.

4.3 The Administration should verify that any recommendations made by MEPC during Basic and Final Approval have been addressed prior to issuing the Type Approval Certificate. In accordance with the BWMS Code (resolution MEPC.300(72)), part 7, the Administration should submit the final report of land-based and shipboard tests with the notification of type approval to the Organization. The reports should be available to Member States.

4.4 The Administration may certify a range of the BWMS capacities employing the same principles and technology, but due consideration should be given to limitations on performance which might arise from scaling up or scaling down.

4.5 The Administration should, in particular, review Standard Operating Procedures (SOP) for which an international standard has yet not been established.

5 APPROVAL PROCESS

5.1 Under the provisions of the BWM Convention, a BWMS is to be approved in accordance with the BWMS Code and, where appropriate, taking into account Procedure (G9).

5.2 The Administration should verify that the following issues have been specifically addressed by the manufacturer and, if the evaluation of the system is carried out by a third-party organization, these issues should be relayed to the Administration to enable a decision on:

- .1 a comprehensive explanation of the physical and/or biochemical treatment processes used by the BWMS to meet the D-2 standard in the BWM Convention. This should be undertaken by the manufacturer and any supporting data should be submitted in writing. Any system which makes use of, or generates, Active Substances, Relevant Chemicals, or free radicals during the treatment process to eliminate organisms in order to comply with the Convention should be submitted to the Organization for review under Procedure (G9), paragraph 3.3;
- .2 whether a BWMS makes use of an Active Substance or not remains the prerogative of the responsible Administration. In making that determination, Administrations should take into account relevant GESAMP-BWWG recommendations and MEPC decisions as to whether a system should be subject to approval under Procedure (G9). When an Administration is unsure of whether a BWMS is subject to Procedure (G9), it may choose to submit such system for review under that Procedure (MEPC 59/24, paragraph 2.16);
- .3 for BWMS that the Administration determines are not subject to Procedure (G9), as provided in paragraph 2.4.11 of the annex to the BWMS Code, the toxicity testing procedures in paragraphs 5.2.2 to 5.2.7 of Procedure (G9) should be used when the system could reasonably be expected to result in changes to the treated water such that adverse impacts to receiving waters might occur upon discharge;
- .4 the approval documents that should include a piping and instrumentation diagram (P&ID) with parts list and material specification. Furthermore, wiring diagrams, function description of the control and monitoring equipment and description of the regulator circuit of the BWMS;
- .5 information on the preliminary testing (methodology, test water composition, salinities tested, sampling, analysis laboratories, etc.);
- .6 accreditation of the BWMS Code land-based testing facility or body including their Quality Management Plan (QMP) and Quality Assurance Project Plan (QAPP) to be used by the manufacturer for land-based testing;
- .7 approval and subsequent verification of the design, construction, operation and functioning of the equipment used for land-based and shipboard testing;

- .8 approval and subsequent verification of the land-based and shipboard test methodology, including the composition of the test water, and specific salinities to be tested which should be in line with the BWMS Code, Procedure (G9) and the *Methodology for information gathering and conduct of work of the GESAMP-BWWG*, as appropriate (waiver for multiple testing required);
- .9 approval and subsequent verification of the methodology used to take and store samples, the laboratory testing, the frequency of sampling and the analysis procedure for samples from land-based and shipboard testing;
- .10 approval and subsequent verification of the design, construction, operation and functioning of the equipment used for testing;
- .11 the list of major components, as defined in the BWMS Code, that are included in the BWMS design;
- .12 if the system is using an Active Substance, the applications for Final Approval will have to be checked and approved by the Administration prior to making a proposal for approval to the Organization. In addition, the cost-recovery fee for the scientific services provided by the GESAMP-BWWG will have to be submitted;
- .13 a safety assessment of the storage and handling of any chemicals is undertaken and approved in line with the technical guidance developed by the Organization (BWM.2/Circ.20);
- .14 a safety and hazard assessment of the installation, operation and maintenance of the BWMS on the shipboard test is undertaken and approved in line with the technical guidance developed by the Organization (BWM.2/Circ.20), and includes as a minimum:
 - .1 any potential impact on crew health and safety; and
 - .2 references to the classification society safety and hazard rules and recommendations;
- .15 all electrical equipment used to operate the BWMS should be of a certified safety type required by the applicable national or international standard in respect of the hazardous areas where it is located; and
- .16 results of environmental testing as specified in part 3 of the annex to the BWMS Code.

5.3 For issuance of the Type Approval Certificate, the Administration should set the following requirements and provisions:

- .1 the validity of the approval should be revisited as appropriate;
- .2 in due time before the expiration of the approval, the manufacturer should prepare a report detailing the experiences with the system, including the results of any scientific research relevant to the system, as well as any results of port State controls, if available;

- .3 the occurrence of any unexpected harmful consequences of the operation of the BWMS should be reported by the manufacturer to the Administration immediately;
- .4 in accordance with the BWMS Code, the Type Approval Certificate should include details on all limiting operating conditions, restrictions and/or system design limitations (SDL) determined by the Administration for the operation of the BWMS;
- .5 an annex to the Type Approval Certificate should contain the test results of each land-based and shipboard test run. Such test results should include at least the numerical salinity, temperature, flow rates, and where appropriate UV transmittance. In addition, these test results should include all other relevant variables;
- .6 the Type Approval Certificate should specify the components of the BWMS that are type approved, including the manufacturer of each component, their operating ranges, including temperature, specific salinity and specify the possibility to use other similar components (e.g. filters) and the criteria for allowing such use;
- .7 a separate Type Approval Certificate should be provided for each type or model of the BWMS. However, if Administrations wish to do otherwise, it is recommended that the different types and models are clearly stated and the test each type and model has undergone clearly referred to with test results, operating ranges, salinity, TRC, etc.;
- .8 all accidents (e.g. accidental exposure, leakage) related to the BWMS should be reported;
- .9 any indications that the system is not performing to the standards set by the BWM Convention, the BWMS Code and/or any additional provisions set by the Administration should be reported by the manufacturer to the Administration immediately;
- .10 the Administration should have the opportunity to revoke the approval if these requirements are not met; and
- .11 MSC.1/Circ.1221 on Validity of Type Approval Certification for marine products should apply.

6 EVALUATION OF MODIFICATIONS TO BWMS WITH EXISTING TYPE APPROVAL

6.1 During the life cycle of a BWMS type approval, it may become necessary, due to supply chain issues, obsolescence, life cycle performance, and/or ability, to improve the performance or cost efficiency of a system that modifications to a type approved BWMS are needed. Modifications may include BWMS design and/or operational parameters, treatment processes, or components included within a type approved BWMS that need to be upgraded, changed or replaced. When evaluating BWMS modifications, the type of component (major or minor) being modified determines the extent of the evaluation necessary to ensure continued effective operation of the BWMS.

6.2 Resolution MEPC.300(72) defines "major component" as "...those components that directly affect the ability of the system to meet the ballast water performance standard described in regulation D-2". Examples of major components may include filters, ultraviolet modules, electrochlorination cells, dosing units, etc.

6.3 Resolution MEPC.300(72) incorporates the term "non-major component" but does not provide a definition. Based on the definition of "major component" and for the purposes of this guidance, "non-major component", also referred to as a "minor component", means "those components that do not directly affect the ability of the system to meet the performance standard described in regulation D-2". Examples of minor components may include pumps, valves, common electrical components (e.g. fuses, circuit breakers), common sensors (e.g. temperature, pressure, salinity, see also appendix, table 3), and cabinetry. Many minor components within a BWMS are considered common marine equipment and may have marine type approval certificates and/or testing reports following IACS UR E10, as applicable.

6.4 The manufacturer, Administration, and, if applicable, the third-party quality assurance organization (e.g. recognized organization, nominated body, classification society, etc.) are encouraged to use figure 1 as a means to identify whether a component is a major or minor component.

6.5 The extent of evaluation for BWMS modifications should be proportional to the modification (e.g. greater potential impact of the modification on BWMS effectiveness, safety or environmental aspects may have more detailed evaluations and/or testing). For minor component modifications when the evaluation indicates that there are no identified direct impacts to the ability of a BWMS to meet the performance standards, no identified impacts to normal BWMS operation, no compromise to ship safety, or no identified impacts to Final Approval aspects under Procedure (G9), a streamlined evaluation process that facilitates time efficient type approval amendments should be implemented. Review of proposed modifications to minor components by the Administration should confirm that normal BWMS operation and/or ship safety will not be compromised. Additional testing and/or evaluation should only be required when functional equivalency has not been demonstrated, or if the review indicates there may be impacts to normal BWMS operation and/or ship safety.

6.6 When evaluating modifications to a BWMS that employs an Active Substance, Administrations should follow BWM.2/Circ.13/Rev.5, annex, section 12, as may be revised.





6.7 Regardless of the type of BWMS modification, the manufacturer should provide to the approving Administration:

- .1 a clear description of the BWMS modification and technical information to support an evaluation of the appropriateness of the modification;
- .2 information on the identification of the component as either major or minor, as applicable;
- .3 the specifications of the current component(s) in the existing BWMS type approval, as applicable;
- .4 the specifications of the proposed new component(s), as applicable; and
- .5 a comparative evaluation to demonstrate the suitability of the modification.

6.8 If the modification involves any major component of the BWMS, the Administration should determine the necessary tests for type approval of the modified BWMS, consistent with the BWMS Code and guidelines developed by the Organization. This may include land-based and/or shipboard testing of the BWMS (full, reduced or modified scope of BWMS Code testing requirements), environmental testing, disinfection by-product and/or whole effluent toxicity testing (as may be applicable to BWMS having Final Approval), operational testing, and/or SDL verification. Approval of the modified BWMS should be based on testing data related to the modified BWMS. A modified BWMS type approval should not be based on prior type approval testing data that is no longer representative of the modified BWMS.

6.9 If the BWMS modification involves a minor component, the Administration should verify that the following items have been addressed by the manufacturer:

- .1 information on type approvals of the proposed new component(s); and
- .2 description demonstrating that the new component does not interfere with the BWMS' ability to meet the D-2 standard and the overall function of the system in the shipboard environment.

6.10 To allow for an efficient documentation and reporting process for BWMS manufacturers with multiple type approvals, the Administration should provide a Type Approval Certificate that includes the approved BWMS modifications. Type Approval Certificates should be maintained by the BWMS manufacturer and provided to ships to which the BWMS modifications are applicable for review during port State control inspections and/or flag State surveys.

6.11 To eliminate duplication of environmental testing of individual components by multiple BWMS manufacturers, environmental testing carried out by another BWMS manufacturer or the original equipment manufacturer (OEM) of individual components should be submitted as part of the evaluation required under paragraphs 6.8 and 6.9 provided that testing meets the requirements of part 3 of the BWMS Code.

6.12 Following completion of modifications to an existing type approval by the issuing Administration, and provided that the review process in figure 1 and the applicable requirements of the BWMS Code and guidelines developed by the Organization have been followed and the BWMS modifications have been determined acceptable, other Administrations, class societies and recognized organizations are encouraged to provide mutual recognition of the modification. Also refer to paragraph 6.9 of the BWMS Code.

6.13 This Guidance should be kept under review, and modified if necessary, considering the experience gained regarding modifications to BWMS with an existing type approval and, in particular, with respect to the identification of major and minor components.

7 REPORTING OF THE TYPE APPROVAL

7.1 The Administration should forward a report of the type approval process to the Organization, including the relevant documentation as specified in part 7 of the annex to the BWMS Code.

7.2 In particular, where under Procedure (G9) the Final Approval has been granted with recommendations by the GESAMP-BWWG, evidence that these recommendations have been satisfactorily addressed at type approval should be provided to the Organization. The report should specify the findings of the Administration together with any non-confidential information taking into account Procedure (G9).

APPENDIX

To provide additional clarity on the types of components identified as "major components" (BWMS Code, definition 3.9) and "minor components" within this Guidance, the following tables of examples have been developed for consideration. The examples are not intended to be exhaustive or representative of all technologies and all components that may be associated with a particular BWMS; however, examples of common components are provided.

Table 1 Example major components			
Chemical injection	Electrochlorination	Mechanical separation	Ultraviolet irradiation
 TRO or relevant sensor (if a part of the system) 	 Electrolytic chamber/cell (if modification alters the technical specification, e.g. geometry anode, chlorine production) TRO sensor 	 Filter (if modification alters the technical specification, e.g. mesh, self-cleaning technology) 	 UV chamber (if modification alters the technical specification of the UV chamber, e.g. geometry, inner surface reflective ability, UV lamp arrangement) UV intensity or UV transmittance sensor (as applicable) UV lamps UV quartz sleeves

Table 2 Examples of changes or modifications affecting major components			
Chemical injection	Electrochlorination	Mechanical separation	Ultraviolet irradiation
 Active substance formulation Software* Dosage 	 Software* Dosage 	 Filter mesh design Filter mesh size Filter manufacturer or separation technology Self-cleaning technology Removal of filter Filter surface area 	 Software* Dosage

Only software modifications that have the potential to directly impact biological efficacy are considered modifications to a major component.

Table 3 Example minor components, similar technical specifications provided			
 Actuation switch Actuation/activation button Alarm horn Cabling Circuit breakers Cleaning-in-place unit Conductivity sensor Conductivity transmitter Dilution blower 	 Electrical cabinetry Filter backflush pump Filter index arm motor Flow meter Fuses Gas detector Heat exchanger (non-pasteurization) HMI screen Junction box 	 Mixing, circulation or injection pump Piping materials Pressure transmitter Program Logic Controller Rectifier Remote operation panel Salinity transmitter Sensor, differential pressure Sensor, temperature 	 Signage Switch, temperature Terminal blocks Touch panel Transformer Valves Water level switch

Components in table 3 may not be considered minor if the Administration determines that they might affect the BWMS' ability to meet the D-2 standard.



4 ALBERT EMBANKMENT LONDON SE1 7SR Telephone: +44 (0)20 7735 7611 Fax: -

KMENT 7SR Fax: +44 (0)20 7587 3210

> HKSRC.2/Circ.1 1 November 2024

F

PROVISIONAL GUIDANCE ON THE IMPLEMENTATION OF THE HONG KONG AND BASEL CONVENTIONS WITH RESPECT TO THE TRANSBOUNDARY MOVEMENT OF SHIPS INTENDED FOR RECYCLING

1 The Marine Environment Protection Committee, at its eighty-second session (30 September to 4 October 2024), approved the *Provisional guidance on the implementation of the Hong Kong and Basel Conventions with respect to the transboundary movement of ships intended for recycling*, as set out in the annex.

2 Member States are encouraged to share their experience with the implementation of requirements and recommendations concerning ship recycling and submit information in that regard to future sessions of the Marine Environment Protection Committee and to relevant meetings under the Basel Convention.



ANNEX

PROVISIONAL GUIDANCE ON THE IMPLEMENTATION OF THE HONG KONG AND BASEL CONVENTIONS WITH RESPECT TO THE TRANSBOUNDARY MOVEMENT OF SHIPS INTENDED FOR RECYCLING

Member States should take into account the following provisional guidance on the implementation of the Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships, 2009 (Hong Kong Convention) and the Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and their Disposal (Basel Convention) with respect to the transboundary movement of ships intended for recycling:

- .1 States that are Parties to the Hong Kong Convention but are not Parties to the Basel Convention should apply the requirements of the Hong Kong Convention;
- .2 States that are Parties to the Basel Convention but are not Parties to the Hong Kong Convention should apply the requirements of the Basel Convention, including its Ban Amendment, if they have expressed their consent to be bound by it; and
- .3 States that are Parties to both the Hong Kong Convention and the Basel Convention, including Parties that have expressed their consent to be bound by the Ban Amendment, with an understanding that the provisions of the Basel Convention should not affect the transboundary movements that take place pursuant to the Hong Kong Convention, should consider notifying the Secretariat of the Basel Convention as follows:

"In accordance with Article 11 of the Basel Convention, the Basel Convention Secretariat is hereby notified that [name of the State that is a Party to both the Hong Kong Convention and the Basel Convention] is a Party to the Hong Kong International Convention for the Safe and Environmentally Sound Recycling of Ships, 2009 (Hong Kong Convention) and will apply the Hong Kong Convention's requirements in respect of transboundary movements of ships^{*} intended to be recycled at a ship recycling facility that has been authorized in accordance with the Hong Kong Convention and is situated under the jurisdiction of a Party to the Hong Kong Convention.

Relevant arrangements have been made to ensure environmentally sound management of hazardous wastes and other wastes (arising from ship recycling) as required by the Basel Convention. Consequently, the provisions of the Basel Convention shall not affect transboundary movements which take place pursuant to the Hong Kong Convention."

^{*} Ships that fall within the scope of Article 3 (Application) of the Hong Kong Convention.



4 ALBERT EMBANKMENT LONDON SE1 7SR Telephone: +44 (0)20 7735 7611 Fax: +44 (0)20 7587 3210

> MEPC.1/Circ.913 21 October 2024

F

GUIDANCE ON THE APPLICATION OF THE AMENDMENTS TO APPENDIX IX OF MARPOL ANNEX VI ON INCLUSION OF DATA ON TRANSPORT WORK AND ENHANCED GRANULARITY IN THE IMO SHIP FUEL CONSUMPTION DATABASE (IMO DCS) AS ADOPTED BY RESOLUTION MEPC.385(81)

1 The Marine Environment Protection Committee, at its eighty-second session (30 September to 4 October 2024), approved the *Guidance on the application of the amendments* to appendix IX of MARPOL Annex VI on inclusion of data on transport work and enhanced granularity in the IMO Ship Fuel Consumption Database (IMO DCS) as adopted by resolution MEPC.385(81), as set out in the annex.

2 Member Governments are invited to bring the annexed Guidance to the attention of masters, seafarers, shipowners, ship operators and other stakeholders concerned.

NAVIGATING THE FUTURE: SAFETY FIRST!

ANNEX

GUIDANCE ON THE APPLICATION OF THE AMENDMENTS TO APPENDIX IX OF MARPOL ANNEX VI ON INCLUSION OF DATA ON TRANSPORT WORK AND ENHANCED GRANULARITY IN THE IMO SHIP FUEL CONSUMPTION DATABASE (IMO DCS) AS ADOPTED BY RESOLUTION MEPC.385(81)

The amended regulations 27.1 and 27.2 of MARPOL Annex VI read as follows:

"1 From calendar year 2019, each ship of 5,000 gross tonnage and above shall collect the data specified in appendix IX to this Annex, for that and each subsequent calendar year or portion thereof, as appropriate according to the methodology included in the SEEMP.

2 Except as provided for in paragraphs 4, 5 and 6 of this regulation, at the end of each calendar year, the ship shall aggregate the data collected in that calendar year or portion thereof, as appropriate."

Regulation 5.4.5 of MARPOL Annex VI reads as follows:

"5 The Administration shall ensure that for each ship to which regulation 27 applies, the SEEMP complies with regulation 26.2 of this Annex. This shall be done prior to collecting data under regulation 27 of this Annex in order to ensure the methodology and processes are in place prior to the beginning of the ship's first reporting period. Confirmation of compliance shall be provided to and retained on board the ship;"

Regulation 26.2 of MARPOL Annex VI reads as follows:

"2 In the case of a ship of 5,000 gross tonnage and above, the SEEMP shall include a description of the methodology that will be used to collect the data required by regulation 27.1 of this Annex and the processes that will be used to report the data to the ship's Administration."

Guidance on application

Within the scope of application of the amendments to appendix IX of MARPOL Annex VI adopted by resolution MEPC.385(81) and aiming to maintain uniform data granularity throughout the collection and reporting process over a calendar year, the term "portion thereof" in regulations 27.1 and 27.2 of MARPOL Annex VI should be applied in such a way that all data portions for the same calendar year are to be collected and reported at the same level of granularity.

Prior to collecting data specified in appendix IX of MARPOL Annex VI as amended by resolution MEPC.385(81), each ship to which regulation 27 applies should have their SEEMP revised to ensure compliance with regulation 26.2 of MARPOL Annex VI, taking into account the 2024 Guidelines for the development of a Ship Energy Efficiency Management Plan (SEEMP) (resolution MEPC.395(82).

In light of this, Administrations are invited to apply the amendments adopted by resolution MEPC.385(81) as follows:

For ships flying the flag of the Administration which implements the amendments early (1 January 2025):

- .1 the SEEMP should undergo revision and verification by the Administration, or its recognized organization, to incorporate a description of the methodology intended for collecting data with enhanced granularity before 1 January 2025 or the delivery date for ships delivered on or after 1 January 2025. Those planning to retrofit flow meters or other methodologies should complete these actions within the same time frame; and
- .2 data will be collected and reported with an enhanced level of granularity throughout the entire year of 2025 and beyond.

For ships flying the flag of the Administration which implements the amendments on the entry-into-force date (1 August 2025):

- .1 the SEEMP should undergo revision and verification by the Administration, or its recognized organization, to incorporate a description of the methodology intended for collecting data with enhanced granularity before 1 January 2026. Those planning to retrofit flow meters or employ other methodologies should complete these actions within the same time frame;
- .2 data will be collected with the existing level of granularity throughout the entire year of 2025 and, therefore, the data reported at the beginning of 2026 will be based on this consistent level. Data will be collected and reported with the enhanced level of granularity from 1 January 2026 and beyond; and
- .3 ships delivered on or after 1 August 2025 should collect data at the enhanced level of granularity from the date of delivery and the data reported at the beginning of 2026 will be based on appendix IX of MARPOL Annex VI in the annex to resolution MEPC.385(81), as this provides consistent data collection and reporting for such ships on or after the entry-into-force date.

ClassNK テクニカルインフォメーション No. TEC-1343 添付5.



図 1: カナダ北極海 ECA の図示



図 2: ノルウェー海 ECA の図示