Subject

Emergency escape breathing devices (EEBD) onboard the Belize flagged vessels



 No.
 TEC-0578

 Date
 21 April 2004

To whom it may concern

The Belize Government has notified ClassNK of the special requirements for EEBDs onboard the Belize flagged vessels, and then the latest requirements are as follows:

Emergency escape breathing devices (EEBD)

- 1. EEBDs should be provided in accommodation spaces as stated below.
 - (1) For cargo ships: 2 EEBDs and 1 spare EEBD.
 - (2) For passenger ships carrying not more than 36 passenger: 2 EEBDs for each main vertical zone, except those defined in the regulation SOLAS II -2/13. 3. 4. 5, and a total of 2 spare EEBDs.
 - (3) For passenger ships carrying more than 36 passengers: 4 EEBDs for each main vertical zone, except those defined in the regulation SOLAS II -2/13. 3. 4. 5, and a total of 2 spare EEBDs.
- 2. EEBDs should be provided in machinery spaces where crew are normally employed or may be present on a routine basis as stated below.
 - (1) Machinery spaces for category A containing internal combustion machinery used for main propulsion:
 - (i) 1 EEBD in the engine control room, if located within the machinery space.
 - (ii) 1 EEBD in workshop areas, if there is, however, a direct access to an escape way from the workshop, an EEBD is not requirement.
 - (iii) 1 EEBD on each deck or platform level near the escape ladder constituting the second means of escape from the machinery space (except an enclosed escape trunk or watertight door at the lower level of the space).
 - (2) Machinery spaces of category A other than those of (1):
 - 1 EEBD, as a minimum, on each deck or platform level near the escape ladder constituting the second means of escape from the machinery space (except an enclosed escape trunk or watertight door at the lower level of the space).

(To be continued)

NOTES:

- ClassNK Technical Information is provided only for the purpose of supplying current information to its readers.
- ClassNK, its officers, employees and agents or sub-contractors do not warrant the accuracy of the information contained herein and are not liable for any loss, damage or expense sustained whatsoever by any person caused by use of or reliance on this information.
- Back numbers are available on ClassNK Internet Homepage (URL: www.classnk.or.jp).

3. Above requirements are required to be applied to all Belize flagged vessels. ClassNK should confirm to comply with the requirements at the first survey on or after 1 July 2004 and report the results in the survey record. In this case, please note that fire control plan is required to be corrected.

This ClassNK Technical Information supersedes the previous ClassNK Technical Information No. TEC-0460 dated 25 May 2002 and replaces the special requirement for this flagged vessel stated in ClassNK Technical Information No. TEC-0467 dated 26 June 2002.

For any questions about the above, please contact:

NIPPON KAIJI KYOKAI (ClassNK)Material and Equipment Department, Administration Center, Head OfficeAddress:4-7 Kioi-cho, Chiyoda-ku, Tokyo 102-8567, JapanTel.:+81-3-5226-2020Fax:+81-3-5226-2057E-mail:eqd@classnk.or.jp