Subject

IACS UI SC213 for non-Japanese flag ships



No. TEC-0684

Date 7 December 2006

To whom it may concern

IACS UI SC213 has been established as an interpretation of SOLAS Reg.III/31.1.4, III/7.2.1.2, III/11.4, III/11.7 and III/16.7 on August 2006. This UI is implemented for ships contracted for construction on or after 1 January 2007.

This UI interprets life rafts, if located at aft/forward end of the ship and at a distance more than 100 m from the closest survival craft, as required by SOLAS Reg.III/31.1.4, shall be regarded as "remotely located survival craft" with regard to SOLAS Reg.III/7.2.1.2. And it says the area where these remotely located survival crafts are stowed shall be provided with:

- 1. At least 2 lifejackets and 2 immersion suits
- Adequate means of illumination, either fixed or portable, which shall be capable of illuminating
 the life raft stowage position as well as the area of water into which the life raft should be
 launched. Portable lights, when used, shall have brackets to permit their positioning on both sides
 of the vessel
- 3. An embarkation ladder or other means of embarkation enabling descent to the water in a controlled manner (e.g. knotted rope) as per SOLAS Reg.III/11.7.

For any questions about the above, please contact:

NIPPON KAIJI KYOKAI (ClassNK)

Material and Equipment Department, Administration Center, Head Office

Address: 4-7 Kioi-cho, Chiyoda-ku, Tokyo 102-8567, Japan

Tel.: +81-3-5226-2020 Fax: +81-3-5226-2057 E-mail: eqd@classnk.or.jp

NOTES:

- ClassNK Technical Information is provided only for the purpose of supplying current information to its readers.
- ClassNK, its officers, employees and agents or sub-contractors do not warrant the accuracy of the information contained herein and are not liable for any loss, damage or expense sustained whatsoever by any person caused by use of or reliance on this information.
- Back numbers are available on ClassNK Internet Homepage (URL: www.classnk.or.jp).